

Fuse-link, 14x51 mm, 16A, gG

Part no. Z-C14/SE-16A/GG

Article no. 112173



Similar to illustration

## Delivery program

Product range			Fuse material
Basic function			Accessories
Basic function			Cylindrical fuse inserts
Utilization category			Utilization category gG (gL)
Size			14 x 51
Rated operational current	$I_e$	A	16
Rated operational voltage	$U_e$	V AC	690

## Technical data

### Electrical

Standards			IEC 60269-1 IEC 60269-2-1
Rated operational voltage	$U_e$	V	
Rated operational voltage	$U_e$	V AC	690
	$U_e$	V AC	
Rated operating voltage	$U_e$	V AC	2 - 32 A: 690 40 - 50 A: 500
Rated frequency	f	Hz	50
Rated frequency	f	Hz	50

## Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55

## Technical data ETIM 5.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss8-27-14-20-02 [AFZ797009])			
Size			14x51 mm
Rated voltage			AC 690 V
Nominal current		A	16
With striker			No