

Fuse-link, DIII, 35A, 500 V, DZ

Part no. Z-DIII/SE-35A/DZ
Article no. 112132



Similar to illustration

Delivery program

Product range			Fuse Bases
Basic function			Accessories
Basic function			Fuse links
Utilization category			Utilization category DZ
Rated operating voltage			500VAC/400 V DC
Rated operational current	I_e	A	35
Fuse cartridge		Size	DIII E33

Technical data

Electrical

Standards			DIN EN 60269-1 (VDE 0636 Part 10), DIN EN 60269-3 (VDE 0636 Part 30), DIN VDE 0636-301, CEE 16, IEC/EN 60269-1, IEC/EN 60269-3
Rated operational voltage	U_e	V	
	U_e	V AC	
Rated operating voltage	U_e	V AC	500
Rated frequency	f	Hz	45 - 65
Rated frequency	f	Hz	45 - 65

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / D-system fuse link (EC000099)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Diazed fuse link (ecl@ss8.1-27-14-20-04 [AFZ799012])			
Construction size			DIII
Nominal rated current		A	35
Nominal rated voltage		V	500
Colour code			Black
Utilization category			-
Release characteristic			-