



Extension terminal, 2.5-35 mm²

Part no. Z-EK/35/UL

Article no. 104901



Powering Business Worldwide™

Delivery program

Basic function			Busbar
Basic function accessories			Extension terminals
Application			Switchgear for industrial and advanced commercial applications
Product range			Z-SV

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)			
Electric engineering, automation, process control engineering / Electrical installation, device / Clamp (not overhead line) / Switch board (ecl@ss8.1-27-14-11-46 [BAA025010])			
Busbar thickness		mm	0 - 0
Busbar width		mm	0 - 0
Suitable for			-
Width clamp		mm	0
Max. conductor cross section		mm ²	0
Max. rated operation current I _e		A	0
Suitable for round conductor connection			Yes
Suitable for sector conductor connection			No
Suitable for strip conductor connection			No

Approvals

Product Standards			IEC/EN 60898; UL 489; CE marking
UL File No.			E257181
UL Category Control No.			NMTR2, DIHS2
CSA File No.			-
CSA Class No.			-
North America Certification			UL recognized
Specially designed for North America			Yes, large creepage and creepage distances
Suitable for			Feeder circuits, branch circuits
Max. Voltage Rating			Refer to main components FAZ, FAZ-NA, FAZ-RT
Degree of Protection			IEC: IP20, UL/CSA Type: -