



Remote testing module, max. 400V-AC, 0.3A, 0.5HP

Part no. Z-FW/030
Article no. 248300
Catalog No. Z-FW/030

Similar to illustration

Delivery program

Basic function			Accessories for residual current circuit breakers Accessories for combined residual-current/power circuit-breakers
Basic function accessories			Remote test module
Application			Switchgear for industrial and advanced commercial applications
Rated fault current	$I_{\Delta N}$	A	0.3
Product range			Accessory
Side mounting			for fitting on left to: FI

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-5
Operating ambient temperature max.		°C	40

Technical data ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary contact unit for distribution board (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ec1@ss8.1-27-14-35-02 [AKE327010])			
Device fitting			Earth leakage switch
Additional equipment			Monitoring unit
Attached at delivery			No
Assembly width (TE)			0.5
Number of normally open contacts			0
Number of normally closed contacts			0
Number of change-over contacts			0
Number of fault-signal switches			0
Rated switch current		A	0
Nominal rated voltage		V	0
Control voltage type			AC
With autotest for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			0
Suitable for max. current main contact unit		A	0

Dimensions

