



## Restarting device-set, 24-48VDC, 6HP

Part no. Z-FW-LPS/MO  
 Article no. 100052  
 Catalog No. Z-FW-LPS/MO


Similar to illustration

## Delivery program

### Notes




#### Pumping full:

Pivot point on left (state of delivery)



#### Pumping dry:

Fulcrum right



#### Case 1

#### Case 2

The actuation mechanism can either be connected to the float switch's actuation lever (configuration 1) or to the float (configuration 2). In configuration 1, the float drives the rod and the actuation lever. In configuration 2, the float and the rod drive the actuation lever. The latter configuration should especially be used in applications with sewage pumps.

## Technical data ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary contact unit for distribution board (EC001286)

Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss8.1-27-14-35-02 [AKE327010])

Device fitting		Earth leakage switch
Additional equipment		Monitoring unit
Attached at delivery		No
Assembly width (TE)		6
Number of normally open contacts		0
Number of normally closed contacts		0
Number of change-over contacts		0
Number of fault-signal switches		0
Rated switch current	A	0
Nominal rated voltage	V	48
Control voltage type		DC
With autotest for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		0
Suitable for max. current main contact unit	A	0