

Impulse relay, 240AC, 1 N/O, 1 N/C, 16A, 50Hz, 1HP



Part no. Z-S240/S0
Article no. 265282

Similar to illustration

Technical data ETIM 6.0

| Devices for distribution board-/surface mounting (EG000062) / Latching relay (EC000188) | | | |
|--|--|----|-------------------|
| Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Latching relay for distribution board (ec1@ss8.1-27-14-23-06 [AFZ818012]) | | | |
| Function | | | Mechanical switch |
| Mounting method | | | DIN rail |
| Width in number of modular spacings | | | 1 |
| Built-in depth | | mm | 60 |
| Number of normally open contacts | | | 1 |
| Number of normally closed contacts | | | 1 |
| Number of change-over contacts | | | 0 |
| Control voltage 1 | | V | 240 - 240 |
| Type of control voltage 1 | | | AC |
| Frequency control voltage 1 | | Hz | 50 - 50 |
| Control voltage 2 | | V | 0 - 0 |
| Type of control voltage 2 | | | AC |
| Frequency control voltage 2 | | Hz | 0 - 0 |
| Rated switch current | | A | 16 |
| Supply voltage | | V | 24 - 240 |
| Voltage type of supply voltage | | | AC |
| Max. incandescent lamp load | | W | 2024 |
| Max. load fluorescent lamp | | VA | 2500 |
| Max. load fluorescent lamp (Duo circuit) | | VA | 2500 |
| Max. load fluorescent lamp (parallel compensated) | | VA | 2500 |
| Max. switching current (cos phi = 0.6) | | A | 24 |
| Manual operation possible | | | Yes |