



## Fuse switch-disconnector with flashing function, 63A, 2p

**Part no.** Z-SLS/CB/2  
**Article no.** 248248

### Delivery program

			With flashing function Current coding through locating inserts
			Standard, empty
Number of poles			2 pole
Rated uninterrupted current $I_u$ at max. cross-section	$I_u$	A	63
Fuse cartridge		Size	D02: 20 - 63 A D01: 2 - 16 A with sleeve locating insert and holding spring

### Technical data

#### Electrical

Number of poles			1P 2P 3P
Rated operational voltage	$U_e$	V	
AC: 1P, 2P, 3P	$U_e$	V AC	400
DC: 1P, 2P		V DC	1P up to 110 / 2P up to 220
Rated operational current	$I_e$	A	63
Rated uninterrupted current	$I_u$	A	63
Rated short-circuit making capacity	$I_{cm}$		50 kAeff
Switching category			AC 22 B
Overvoltage category			IV
Rated impulse withstand voltage	$U_{imp}$	kV	6
Current heat loss per contact at $I_e$		W	0.5
Power loss			
Heat dissipation per contact with fuse link at $I_e$		W	7.5

#### Mechanical

Standard front dimension		mm	45
Enclosure height		mm	86
Mounting width		mm	27/per pole (1.5 SU)
Weight		g	1P 120 2P 230 3P 350
Mounting			Quick attachment for top-hat rail IEC/EN 60715
Degree of protection			
Integrated			IP20
Terminals			Lift terminals
Terminal capacities		mm <sup>2</sup>	
Solid		mm <sup>2</sup>	1.5 - 35
Temperature range		°C	-25 ... +60
Flammability classification according to UL94			V0, glow-wire test 960°C
Terminal screw tightening torque		Nm	max. 4.5
Overvoltage category/pollution degree			III/3
Track resistance			CTI 600

#### Relay section mechanical

Terminals			Lift terminals
-----------	--	--	----------------

### Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / D0-system switch disconnector (EC000277)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Neozed switch disconnector (ecl@ss8.1-27-14-21-10 [AKE282010])			
Number of poles			2

Construction size		D02
Nominal rated voltage	V	400
Nominal rated current	A	63