

0801855

https://www.phoenixcontact.com/us/products/0801855

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plastic label with drill hole, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: adhesive, lettering field size: 45 x 10 mm, Number of individual labels: 500

Your advantages

- The EMLP ... self-adhesive markers are particularly suited to marking electrical components, devices, and buttons
- The markers meet the same standards as the engraved labels, they provide high-quality visuals
- · Quick and inexpensive marking with THERMOMARK ... roll printers from Phoenix Contact
- · When combined with the right ink ribbon, the marking is highly resistant to solvents and mechanical influences
- · Labeling service: Phoenix Contact can custom-label all EMLP ... markers in accordance with your requirements

Commercial data

Item number	0801855
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BG16
Product key	BG2411
Catalog page	Page 331 (C-3-2019)
GTIN	4046356783071
Weight per piece (including packing)	650.8 g
Weight per piece (excluding packing)	650.8 g
Customs tariff number	39269097
Country of origin	PL



0801855

https://www.phoenixcontact.com/us/products/0801855

Technical data

Product properties

Product type	Device marking	
Marking		
Number of individual labels	500	
Number of individual labels per row	1	
Identification technology	Thermal transfer for rolls	

Mounting

Mounting type	adhesive
---------------	----------

Material specifications

Foil strength	50 μm
Adhesive strength	20 μm
Adhesive	Acrylic
Color	white
Material	Polyester
Components	Silicone-free

Environmental and real-life conditions

Rating 150 °C (180 °C)

Test for substances that would hinder coating with paint or varnish		
Result	Test passed	
Test for substances that would hinder coating with paint or varnish		
Result	Test passed	
Scratch test for the determining scratch resistance		
Specification	DIN EN ISO 1518-1:2019-10 (following)	
Requirements	≥ 5 N	
Result	Test passed	
Tesafilm test		
Specification	DIN EN ISO 2409:2013 (following)	
Result	Test passed	
UV resistance		
Specification	ISO 4892-2:2013-03 (following)	
Result	Test passed	
Test duration	96 h	
Temperature resistance		
Specification	ANSI/UL 969-2018:03 (following)	
Test duration	240 h	

Test passed



0801855

https://www.phoenixcontact.com/us/products/0801855

Specification	ISO 175:2010 (following)
Test duration	168 h
Diesel [CAS No. 68476-34-6]	Test passed
IRM 901	Test passed
IRM 902	Test passed
Testing in a condensation changing climate in the presence of sulfu	ur dioxide
Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2
Salt spray test	
Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h
Ambient conditions	
Ambient temperature (operation)	-40 °C 120 °C
Ambient temperature (assembly)	> 18 °C
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 % (Storage in a dry and dark place in the original packaging is recommended)
Shelf life	12 months
imensions	
Width	46 mm
Length	46 mm
tandards and regulations	
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
otes	
General	For the THERMOMARK ROLL and THERMOMARK ROLL 2.0 roll printers, this material can only be processed with an external media hub.



0801855

https://www.phoenixcontact.com/us/products/0801855

Classifications

ECLASS

	ECLASS-11.0	27281103
	ECLASS-12.0	27281103
	ECLASS-13.0	27281103
ETIM		
	ETIM 9.0	EC001288
UNSPSC		
	UNSPSC 21.0	39131500

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com