

MM-WML 3 (EX10)R C1 WH/BK - Cable marker label



0803931

<https://www.phoenixcontact.com/us/products/0803931>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable marker label, Roll, white/black, unlabeled, can be labeled with: THERMOFOX, THERMOMARK GO, THERMOMARK GO.K, mounting type: adhesive, cable diameter range: 2 .. . 3 mm, lettering field size: continuous x 8 mm, Number of individual labels: 1

Your advantages

- High-quality and solvent-resistant marking solution for industrial applications that is created by means of thermal transfer printing
- Thanks to the continuous format, a wrap-around label of the appropriate width can be created flexibly for the relevant application
- Easy and efficient material cartridge system: Includes both the material to be printed and the corresponding ink ribbon
- No visible difference between retrospective marking and existing markings created with a desktop roll printer
- The transparent protective foil is wound over the marking and provides permanent protection against contamination and abrasion
- The wrap-around labels do not add bulk, which means that the cable can still be drawn through cable ducts, for example
- The material is cUL certified

Commercial data

Item number	0803931
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BG23
Product key	BG221E
Catalog page	Page 45 (C-3-2019)
GTIN	4055626212111
Weight per piece (including packing)	80 g
Weight per piece (excluding packing)	77.8 g
Customs tariff number	96121010
Country of origin	CN

Technical data

Product properties

Product type	Conductor marking
Type	Label

Marking

Number of individual labels	1
Number of individual labels per row	1
Identification technology	Thermal transfer

Dimensions

Width	18 mm
Length	6.5 m

External dimensions

Outside diameter	0 mm ... 3 mm
------------------	---------------

Material specifications

RoHS compliant	yes
Adhesive	Acrylic
Color	white/black
Material	Vinyl polymer
Components	Free from silicone and cadmium

Cable/line

External cable diameter	2 mm ... 3 mm
-------------------------	---------------

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-1):2011-07
	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl [CAS No. 67-63-0]	Test passed
n-Hexane [CAS No. 110-54-3]	Test passed
Water + Petroleum ether [CAS No. 64742-82-1]	Test passed

MM-WML 3 (EX10)R C1 WH/BK - Cable marker label



0803931

<https://www.phoenixcontact.com/us/products/0803931>

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
Recommended storage conditions	21 °C / 50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	21 °C
Recommended humidity (storage/transport)	50 %
Shelf life	6 months

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Mounting

Mounting type	adhesive
---------------	----------

MM-WML 3 (EX10)R C1 WH/BK - Cable marker label



0803931

<https://www.phoenixcontact.com/us/products/0803931>

Classifications

ECLASS

ECLASS-11.0	27281102
ECLASS-12.0	27281102
ECLASS-13.0	27281102

ETIM

ETIM 9.0	EC001530
----------	----------

UNSPSC

UNSPSC 21.0	39131500
-------------	----------

MM-WML 3 (EX10)R C1 WH/BK - Cable marker label



0803931

<https://www.phoenixcontact.com/us/products/0803931>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com