

THERMOMARK GO ACCU - Battery



0805009

<https://www.phoenixcontact.com/us/products/0805009>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Battery for mobile operation of the THERMOMARK GO and THERMOMARK GO.K / THERMOFOX printers.

Commercial data

Item number	0805009
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BG03
Product key	BG122Z
Catalog page	Page 43 (C-3-2019)
GTIN	4055626269139
Weight per piece (including packing)	117 g
Weight per piece (excluding packing)	116 g
Customs tariff number	85076000
Country of origin	CN

THERMOMARK GO ACCU - Battery



0805009

<https://www.phoenixcontact.com/us/products/0805009>

Technical data

Product properties

Product type	Printing system accessories
Battery-operated voltage	7.40 V

Electrical properties

Battery

Battery capacity	2.60 Ah
------------------	---------

Energy storage

Battery capacity	2.6 Ah
Battery technology	Lithium-Ion

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	5 °C ... 40 °C
Ambient temperature (storage/transport)	23 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Shelf life	1 Year

THERMOMARK GO ACCU - Battery



0805009

<https://www.phoenixcontact.com/us/products/0805009>

Classifications

ECLASS

ECLASS-11.0	21052902
ECLASS-12.0	21052902
ECLASS-13.0	21052902

ETIM

ETIM 9.0	EC001199
----------	----------

UNSPSC

UNSPSC 21.0	26111700
-------------	----------

THERMOMARK GO ACCU - Battery



0805009

<https://www.phoenixcontact.com/us/products/0805009>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com