

# ESL 26X6 CUS - Insert strip

0824400

<https://www.phoenixcontact.com/us/products/0824400>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Insert strip, Sheet, can be ordered: Sheet, white, labeled according to customer specifications, perforated, mounting type: insert, lettering field size: 26 x 6 mm, Number of individual labels: 266



## Your advantages

- Insert labels for plastic cable markers
- Marking label for GBS-ZB/26x6 terminal strip marker carriers

## Commercial data

Item number	0824400
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	BG8114
GTIN	4046356352710
Weight per piece (including packing)	13.6 g
Weight per piece (excluding packing)	9 g
Country of origin	PL

# ESL 26X6 CUS - Insert strip



0824400

<https://www.phoenixcontact.com/us/products/0824400>

## Technical data

### Product properties

Product type	Labeled terminal marker
Area of application	Phoenix Contact: Marker strips for GBS-ZB/26x6 terminal strip marker carriers

### Marking

Number of individual labels	266
Number of individual labels per row	7
Identification technology	Plotter

### Mounting

Mounting type	insert
---------------	--------

### Material specifications

Color	white
Material	Polyester foil
Components	free from silicone and halogen

### Environmental and real-life conditions

#### Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

#### Scratch test for the determining scratch resistance

Specification	DIN EN ISO 1518-1:2011 (following)
Requirements	≥ 5 N
Result	Test passed

#### Tesafilm test

Specification	DIN EN ISO 2409:2013 (following)
Result	Test passed

#### UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

#### Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

#### Salt spray test

Specification	DIN EN 60068-2-11:2000-02
---------------	---------------------------

# ESL 26X6 CUS - Insert strip



0824400

<https://www.phoenixcontact.com/us/products/0824400>

Result	Test passed
Test duration	96 h

## Ambient conditions

Ambient temperature (operation)	-40 °C ... 100 °C
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 % (Storage in a dry and dark place in the original packaging is recommended)

## Dimensions

Width	26 mm
Length	6 mm

## Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

# ESL 26X6 CUS - Insert strip



0824400

<https://www.phoenixcontact.com/us/products/0824400>

## Classifications

### ECLASS

ECLASS-11.0	27281106
ECLASS-12.0	27281106
ECLASS-13.0	27281106

### ETIM

ETIM 9.0	EC001530
----------	----------

### UNSPSC

UNSPSC 21.0	39131700
-------------	----------

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)