

# HC-STA-B10-HHWD-1STM32-EL-AL - Housing



1412609

<https://www.phoenixcontact.com/us/products/1412609>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sleeve housing B10, with double locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, lateral, 1x M32, height: 72 mm, cable gland: none, Standard

## Your advantages

- Good shielding in the event of electromagnetic interference

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1412609             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 1 pc                |
| Sales key                            | BF56                |
| Product key                          | BF7APB              |
| Catalog page                         | Page 614 (C-2-2019) |
| GTIN                                 | 4055626059365       |
| Weight per piece (including packing) | 204.1 g             |
| Weight per piece (excluding packing) | 204 g               |
| Customs tariff number                | 85389099            |
| Country of origin                    | CN                  |

# HC-STA-B10-HHWD-1STM32-EL-AL - Housing



1412609

<https://www.phoenixcontact.com/us/products/1412609>

## Technical data


### Notes

|         |   |
|---------|---|
| General | for contact inserts HC-B10, BB18, DD42, M, K8/24, HV03                                    |
| General | also available as a powder-coated or color version: 1372729 HC-STA-B10-HHWD-1STM32-EL/... |

### Product properties

|                              |                            |
|------------------------------|----------------------------|
| Type                         | B10                        |
| Product type                 | Housing with locking latch |
| Application                  | Standard                   |
| No. of cable outlets         | 1                          |
| Type of the screw connection | 1x M32                     |
| Housing type                 | Sleeve housing             |
| Cable outlet                 | lateral                    |
| Pg screw connection          | none                       |

### Dimensions

|                     |  |
|---------------------|--|
| Dimensional drawing |  |
| Width               | 44 mm  |
| Height              | 72 mm  |
| Length              | 73 mm  |

### Material specifications

|  |   |
|--|---|
| Flammability rating according to UL 94 | V0 (Interlock)                          |
| Housing surface material               | uncoated                                |
| Locking latch material                 | PA                                      |
| Impact strength                        | IK09                                    |
| Housing material                       | Die-cast aluminum, salt water resistant |

### Mechanical properties

#### Mechanical data

|                              |        |
|------------------------------|--------|
| Type of the screw connection | 1x M32 |
| Locking type                 | Latch  |

### Environmental and real-life conditions

#### Ambient conditions

|                      |      |
|----------------------|------|
| Degree of protection | IP66 |
|                      | IP67 |

# HC-STA-B10-HHWD-1STM32-EL-AL - Housing



1412609

<https://www.phoenixcontact.com/us/products/1412609>

|                                 |                   |
|---------------------------------|-------------------|
| Enclosure rating (NEMA)         | 4 (UL 50e)        |
|                                 | 4X (UL 50e)       |
|                                 | 12 (UL 50e)       |
| Impact strength                 | IK09              |
| Ambient temperature (operation) | -40 °C ... 125 °C |

# HC-STA-B10-HHWD-1STM32-EL-AL - Housing



1412609

<https://www.phoenixcontact.com/us/products/1412609>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27440202 |
| ECLASS-12.0 | 27440202 |
| ECLASS-13.0 | 27440202 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000437 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 31261500 |
|-------------|----------|

Environmental product compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)