

# G-ESIS-M12-S68L-PEPDS-BK - Cable gland



1415106

<https://www.phoenixcontact.com/us/products/1415106>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable gland, material for screw connection: PA, application: Ex, external cable diameter 3 mm ... 6 mm, shielding: no, connecting thread: M12 x 1.5, color: jet black, with flat gasket

## Product description

Cable gland, with flat gasket

## Your advantages

- Glow-wire test: 750°C
- Weatherproof sealing material
- Halogen-free

## Commercial data

Item number	1415106
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BF68
Product key	BF7DDX
Catalog page	Page 650 (C-3-2019)
GTIN	4055626037684
Weight per piece (including packing)	9 g
Weight per piece (excluding packing)	8.55 g
Customs tariff number	39269097
Country of origin	DE

# G-ESIS-M12-S68L-PEPDS-BK - Cable gland



1415106

<https://www.phoenixcontact.com/us/products/1415106>

## Technical data


### Product properties

Product type	Full screw connection
Application	Ex
No. of conductors	1
Manufacturer	WISKA
Manufacturer Designation	ESKE/1-L-e 12
Shielded	no

### Ex data

Cable types that can be used	for unarmored cables
Suited for EX-applications	yes

### Dimensions

Dimensional drawing	
Length	34 mm
Length of the connecting thread	15 mm
Hole diameter	12.1 mm ... 12.3 mm
Wrench size, union nut	16 mm
Wrench size, support	16 mm
Hexagon angular dimension	18 mm
Thread type connection side	M12 x 1.5
Thread pitch	1.5 mm

### Connection data

Tightening torque	2 Nm (Support sleeve)
-------------------	-----------------------

### Material specifications

Color	black (RAL 9005)
Material Screw connection	PA
Seal material Cable seal	EPDM
Glow wire ignition temperature GWIT according to EN 60695-2-13	750
Material for screw connection	PA

### Cable/line

External cable diameter ( )	3 mm ... 6 mm
-----------------------------	---------------

# G-ESIS-M12-S68L-PEPDS-BK - Cable gland



1415106

<https://www.phoenixcontact.com/us/products/1415106>

Halogen-free	yes
--------------	-----

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP66
	IP68 (5 bar / 0.5 h)
Ambient temperature (operation)	-40 °C ... 75 °C (static (see prototype test report +15°C ... +65°C at impact energy of 4J))

## Approvals

ATEX	II 2 G Ex e IIC Gb, II 2 D Ex tb IIIC Db
IECEX	Ex e IIC Gb, Ex tb IIIC Db

# G-ESIS-M12-S68L-PEPDS-BK - Cable gland



1415106

<https://www.phoenixcontact.com/us/products/1415106>

## Classifications

### ECLASS

ECLASS-11.0	27144432
ECLASS-12.0	27140801
ECLASS-13.0	27140802

### ETIM

ETIM 9.0	EC000441
----------	----------

### UNSPSC

UNSPSC 21.0	39121300
-------------	----------

# G-ESIS-M12-S68L-PEPDS-BK - Cable gland



1415106

<https://www.phoenixcontact.com/us/products/1415106>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)