

G-ESIS-M40-M68L-NEPDS-S - Cable gland



1415129

<https://www.phoenixcontact.com/us/products/1415129>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable gland, material for screw connection: Brass, nickel-plated, application: Ex, external cable diameter 16 mm ... 28 mm, shielding: no, connecting thread: M40 x 1.5, color: silver, with O-ring

Your advantages

- Dust protection during storage and transport provided by a dust cap.
- Weatherproof sealing material
- Halogen-free

Commercial data

Item number	1415129
Packing unit	5 pc
Minimum order quantity	5 pc
Sales key	BF68
Product key	BF7DDX
Catalog page	Page 651 (C-3-2019)
GTIN	4055626037899
Weight per piece (including packing)	223.22 g
Weight per piece (excluding packing)	223.22 g
Customs tariff number	74198090
Country of origin	DE

G-ESIS-M40-M68L-NEPDS-S - Cable gland



1415129
<https://www.phoenixcontact.com/us/products/1415129>

Technical data

Product properties

Product type	Full screw connection
Application	Ex
No. of conductors	1
Manufacturer	WISKA
Manufacturer Designation	EMSKE-L 40
Shielded	no

Ex data

Cable types that can be used	for unarmored cables
Suited for EX-applications	yes

Dimensions

Dimensional drawing	
Length	51 mm
Length of the connecting thread	15 mm
Hole diameter	40.1 mm ... 40.3 mm
Wrench size, union nut	46 mm
Wrench size, support	46 mm
Hexagon angular dimension	51 mm
Thread type connection side	M40 x 1.5
Thread pitch	1.5 mm

Connection data

Tightening torque	20 Nm (Support sleeve)
-------------------	------------------------

Material specifications

Color	Brass
Material Compression ring	PA
Seal material Cable seal	EPDM
Material for screw connection	Brass, nickel-plated

Cable/line

External cable diameter ()	16 mm ... 28 mm
-----------------------------	-----------------

Environmental and real-life conditions

G-ESIS-M40-M68L-NEPDS-S - Cable gland



1415129

<https://www.phoenixcontact.com/us/products/1415129>

Ambient conditions

Degree of protection	IP66
	IP68 (5 bar / 0.5 h)
Ambient temperature (operation)	-40 °C ... 75 °C (static)

Approvals

ATEX	II 2 G/D EEx e II IP68
IECEX	Ex e IIC Gb, Ex tb IIIC Db

G-ESIS-M40-M68L-NEPDS-S - Cable gland



1415129

<https://www.phoenixcontact.com/us/products/1415129>

Classifications

ECLASS

ECLASS-11.0	27144432
ECLASS-12.0	27140801
ECLASS-13.0	27140802

ETIM

ETIM 9.0	EC000441
----------	----------

UNSPSC

UNSPSC 21.0	39121300
-------------	----------

G-ESIS-M40-M68L-NEPDS-S - Cable gland



1415129

<https://www.phoenixcontact.com/us/products/1415129>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com