

G-ESISEC-M25-M68N-NEPDS-S - Cable gland



1415165

<https://www.phoenixcontact.com/us/products/1415165>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable gland, material for screw connection: Brass, nickel-plated, application: Ex, external cable diameter 10 mm ... 17 mm, shielding: yes, connecting thread: M25 x 1.5, color: silver, with O-ring

Your advantages

- Dust protection during storage and transport provided by a dust cap.
- Weatherproof sealing material
- Halogen-free

Commercial data

Item number	1415165
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BF68
Product key	BF7DDX
Catalog page	Page 651 (C-3-2019)
GTIN	4055626037950
Weight per piece (including packing)	81.29 g
Weight per piece (excluding packing)	76 g
Customs tariff number	74198090
Country of origin	DE

G-ESISEC-M25-M68N-NEPDS-S - Cable gland



1415165

<https://www.phoenixcontact.com/us/products/1415165>

Technical data

Mounting

Assembly instructions	Mounting the screw connection: <ul style="list-style-type: none">- Mount cable gland support- Strip outer cable sheath. Expose around 7 mm of the cable shield.- Push the outer cone over the braided shield- Push the inner cone under the shield- Insert both, together with the cable, in the mounted screw connection support- Tighten union nut with the required torque
-----------------------	--

Product properties

Product type	Full screw connection
Application	Ex
No. of conductors	1
Manufacturer	WISKA
Manufacturer Designation	EMSKE-L 25 EMV-Z
Shielded	yes

Ex data

Cable types that can be used	for unarmored cables
Suited for EX-applications	yes

Dimensions

Dimensional drawing	
Length	38 mm
Length of the connecting thread	12 mm
Hole diameter	25.1 mm ... 25.3 mm
Wrench size, union nut	29 mm
Wrench size, support	29 mm
Hexagon angular dimension	32 mm
Thread type connection side	M25 x 1.5
Thread pitch	1.5 mm

Connection data

Tightening torque	10 Nm (Support sleeve)
-------------------	------------------------

Material specifications

G-ESISEC-M25-M68N-NEPDS-S - Cable gland



1415165

<https://www.phoenixcontact.com/us/products/1415165>

Color	Brass
Material Compression ring	PA
Seal material Cable seal	EPDM
Material for screw connection	Brass, nickel-plated

Cable/line

External cable diameter ()	10 mm ... 17 mm
-----------------------------	-----------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP68 (5 bar / 0.5 h)
Ambient temperature (operation)	-40 °C ... 75 °C (static)

Approvals

ATEX	II 2 G/D EEx e II IP68
IECEX	Ex e IIC Gb, Ex tb IIIC Db

G-ESISEC-M25-M68N-NEPDS-S - Cable gland



1415165

<https://www.phoenixcontact.com/us/products/1415165>

Classifications

ECLASS

ECLASS-11.0	27144432
ECLASS-12.0	27140801
ECLASS-13.0	27140802

ETIM

ETIM 9.0	EC000441
----------	----------

UNSPSC

UNSPSC 21.0	39121300
-------------	----------

G-ESISEC-M25-M68N-NEPDS-S - Cable gland



1415165

<https://www.phoenixcontact.com/us/products/1415165>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com