

1416354

https://www.phoenixcontact.com/us/products/1416354

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Connector set, number of positions: 10, connection method: Push-in connection, connection cross section: AWG 26- 14

Commercial data

Item number	1416354
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF63
Product key	BF7AFX
Catalog page	Page 639 (C-2-2017)
GTIN	4055626071251
Weight per piece (including packing)	489.4 g
Weight per piece (excluding packing)	492.1 g
Customs tariff number	85366990
Country of origin	CN



1416354

https://www.phoenixcontact.com/us/products/1416354

Set consists of

HC-B10-I-PT-F - Contact insert

1407729

https://www.phoenixcontact.com/us/products/1407729



Contact insert, number of positions: 10+PE, size: B10, number of connections per position: 1, Socket, Push-in connection, 500 V, 16 A, 0.14 $\rm mm^2$... 2.5 $\rm mm^2$, application: Power

HC-B10-I-PT-M - Contact insert

1407730

https://www.phoenixcontact.com/us/products/1407730



Contact insert, number of positions: 10+PE, size: B10, number of connections per position: 1, Pin, Push-in connection, 500 V, 16 A, 0.14 $\rm mm^2$... 2.5 $\rm mm^2$, application: Power



1416354

https://www.phoenixcontact.com/us/products/1416354

HC-STA-B10-BWSC-ELC-AL - Housing

1411321

https://www.phoenixcontact.com/us/products/1411321



Panel mounting base B10, with single locking latch, material: Die-cast aluminum, salt water resistant, protective cover material: PC, height: 30.5 mm, cable gland: none, protective cover: yes, Standard, with flat gasket

HC-STA-B10-HLFS-1STM25-EL-AL - Housing

1412625

https://www.phoenixcontact.com/us/products/1412625



Sleeve housing B10, for single locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, lateral, 1x M25, height: 57 mm, cable gland: none, Standard



1416354

https://www.phoenixcontact.com/us/products/1416354

G-INS-M25-M68N-NNES-S - Cable gland

1411165

https://www.phoenixcontact.com/us/products/1411165



Cable gland, material for screw connection: Brass, nickel-plated, external cable diameter 11 mm ... 17 mm, shielding: no, connecting thread: M25 x 1.5, color: silver, with O-ring



1416354

https://www.phoenixcontact.com/us/products/1416354

Technical data

Product properties

Туре	B10		
Product type	Connector set		
Number of positions	10		
Connection profile	10+PE		
Application	Standard		
No. of cable outlets	1		
Housing type	Complete housing		
Seal present	yes		
Protective cover	yes		
Series	HC-B		
Insulation characteristics			
Overvoltage category	III		
Degree of pollution	3		

Electrical properties

Rated voltage (III/3)	500 V
Rated surge voltage	6 kV
Rated current	16 A

Connection data

Connection method	Push-in connection
Connection technology	Push-in connection
Conductor cross section	0.14 mm ² 2.5 mm ² (with ferrule)
	0.14 mm ² 2.5 mm ² (with ferrule)
Connection cross section AWG	26 14
Stripping length	8 mm 10 mm

Dimensions

Dimensional drawing	89 65 65 04.5
Width	53 mm
Height	87.5 mm
Length	93.5 mm
Drill hole distance, horizontal	83 mm
Drill hole distance, vertical	32 mm
Hole diameter	4.5 mm



1416354

https://www.phoenixcontact.com/us/products/1416354

Installation dimensions

Width of the assembly cutout	35 mm
Length of the assembly cutout	65 mm

Material specifications

Material Housing	Die-cast aluminum, saltwater-resistant
Material Protective cover	PA
Flammability rating according to UL 94	V0
Seal material Profile gasket	NBR
Seal material Flat gasket	NBR
Contact material	Copper alloy
Contact surface material	Ag
Contact carrier material	PC
Locking latch material	PA
Impact strength	IK08

Cable/line

External cable diameter ()	11 mm 17 mm
	14 mm 17 mm (for UL 514 B)

Mechanical properties

Mechanical data

Locking type	Latch
Insertion/withdrawal cycles	≥ 500

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP67
Impact strength	IK08
Ambient temperature (operation)	-40 °C 100 °C

Mounting

Mounting type	Screw mounting
Assembly instructions	Coding also using the CP-HC (1686478) coding profiles. HC-B6 / HC-B10for two coding profiles. HC-B16/ HC-B24for four coding profiles.
	Connectors may only be operated when there is no load/the power is switched off. Can be used for solid wires and stranded wires with ferrule.



1416354

https://www.phoenixcontact.com/us/products/1416354

Classifications

ECLASS

	ECLASS-11.0	27440101			
	ECLASS-12.0	27440113			
	ECLASS-13.0	27440113			
ΕT	ETIM				
	ETIM 9.0	EC002636			
UNSPSC					
	UNSPSC 21.0	39121400			



1416354

https://www.phoenixcontact.com/us/products/1416354

Environmental product compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com