

HC-M-04-KT-F - Contact insert module



1417370

<https://www.phoenixcontact.com/us/products/1417370>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact insert module, number of positions: 4xKOAX, power contacts: 0, control contacts: 4, Socket, Soldering and crimp connection, 48 V, 2 A, 0.2 mm² ... 0.8 mm², application: Signal

Commercial data

Item number	1417370
Packing unit	5 pc
Minimum order quantity	5 pc
Sales key	BF62
Product key	BF7ACE
Catalog page	Page 589 (C-2-2019)
GTIN	4055626112527
Weight per piece (including packing)	7.18 g
Weight per piece (excluding packing)	7.1 g
Customs tariff number	85389099
Country of origin	PL

Technical data

Notes

General	For HEAVYCON housings type B6 to B48, HC-M-B...MF... module carrier frame required, crimp contacts HC-M-04-KOAX... (crimp contacts not included in the scope of delivery)
General	Connectors may be operated only when there is no load/voltage.
General	It is imperative that guide pins (HC-CST) and sockets (HC-CBU) are used to prevent tip collision due to misalignment.
General	The designations "female" and "male" are used differently for coaxial contacts than for single-position contacts. The correct accessories can be found in the e-shop.

Product properties

Product type	Coaxial insert, modular
Number of positions	4
Connection profile	4xKOAX
Contact numbering	1 - 4
Application	Signal
Number of module slots	1
No. of power contacts	0
No. of control contacts	4
Contact material type	turned
Series	HC-M-04-KOAX

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated voltage (III/3)	48 V
Rated surge voltage	0.8 kV
Rated current	1.5 A
Contact resistance, phase conductor	≤ 3 mΩ
Contact resistance, inner conductor	≤ 10 mΩ
Insulation resistance	≥ 10 GΩ

Connection data

Connection technology

Connection technology	Soldering and crimp connection
-----------------------	--------------------------------

Conductor connection

Conductor cross section	0.2 mm ² ... 0.8 mm ²
Connection cross section AWG	24 ... 18
Stripping length of the individual wire	2.5 mm ±0.5 mm


HC-M-04-KT-F - Contact insert module



1417370

<https://www.phoenixcontact.com/us/products/1417370>

Dimensions

Dimensional drawing	
Width	34.2 mm
Height	32.6 mm
Length	14.6 mm

Mechanical characteristics

Contact diameter	4.8 mm
------------------	--------

Material specifications

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Au
Contact carrier material	PC
Standards/regulations	PC: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)

Cable/line

Stripping length of the individual wire	2.5 mm ±0.5 mm
---	----------------

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

Standards and regulations

Testing

Standards/regulations	PC: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)
-----------------------	---

Mounting

Assembly instructions	To ensure correct use, installation in housing with IP54 protection or better is required For HC-M-04-ST-KOAX... contacts
-----------------------	--

HC-M-04-KT-F - Contact insert module



1417370

<https://www.phoenixcontact.com/us/products/1417370>

Classifications

ECLASS

ECLASS-11.0	27440217
ECLASS-12.0	27440217
ECLASS-13.0	27440217

ETIM

ETIM 9.0	EC000438
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

HC-M-04-KT-F - Contact insert module



1417370

<https://www.phoenixcontact.com/us/products/1417370>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com