


# CUC-DST-GPME-A/DSSC15 - D-SUB sleeve housings



1419718

<https://www.phoenixcontact.com/us/products/1419718>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



D-SUB sleeve housings, degree of protection: IP20, material: ABS, metal-plated, cable outlet: angled, housing size: 2, color: Bare metallic

## Your advantages

- Easy to mount thanks to preassembled locking screws
- Angled conductor entry
- Antimagnetic plastic housing

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1419718       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | AB19          |
| Product key                          | ABNCAE        |
| GTIN                                 | 4055626187884 |
| Weight per piece (including packing) | 18.2 g        |
| Weight per piece (excluding packing) | 18 g          |
| Customs tariff number                | 85389099      |
| Country of origin                    | DE            |

1419718

<https://www.phoenixcontact.com/us/products/1419718>

## Technical data


### Product properties

|                      |                 |
|----------------------|-----------------|
| Type                 | D-SUB           |
| Product type         | Sleeve housings |
| No. of cable outlets | 1               |
| Cable outlet         | angled          |

### Connection data

|              |          |
|--------------|----------|
| Screw thread | 4-40 UNC |
|--------------|----------|

### Dimensions

|                     |  |
|---------------------|--|
| Dimensional drawing |  <p>The drawing shows two views of the sleeve housing. The side view (left) shows a height of 16.2<sup>+0.3</sup> mm and a total width of 41.2<sup>+0.3</sup> mm. The front view (right) shows a depth of 49.4<sup>+0.3</sup> mm. Other dimensions include 16<sup>+0.3</sup> mm, 33.3<sup>+0.1</sup> mm, and a cable outlet diameter of 3.5-5.5 mm.</p> |
| Width               | 41.2 mm  |
| Height              | 16.2 mm  |
| Depth               | 49.4 mm  |

### Material specifications

|  |                   |
|--|-------------------|
| Color                                  | Bare metallic     |
| Flammability rating according to UL 94 | V0                |
| Housing surface material               | metal-plated      |
| Housing material                       | ABS, metal-plated |

### Cable/line

|                             |                   |
|-----------------------------|-------------------|
| External cable diameter ( ) | 3.5 mm ... 8.6 mm |
|-----------------------------|-------------------|

### Environmental and real-life conditions

#### Ambient conditions

|                                 |                  |
|---------------------------------|------------------|
| Degree of protection            | IP20             |
| Ambient temperature (operation) | -35 °C ... 95 °C |

### Mounting

|               |                         |
|---------------|-------------------------|
| Mounting type | Screw locking mechanism |
|---------------|-------------------------|

1419718

<https://www.phoenixcontact.com/us/products/1419718>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27440202 |
| ECLASS-12.0 | 27440202 |
| ECLASS-13.0 | 27440202 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000437 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 31261500 |
|-------------|----------|

1419718

<https://www.phoenixcontact.com/us/products/1419718>

## Environmental product compliance

|            |  |
|------------|--|
| REACH SVHC | Lead 7439-92-1   |
| China RoHS | Environmentally Friendly Use Period = 50 years   |
|            | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)