

1623888

https://www.phoenixcontact.com/us/products/1623888

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



CHARX connect basic, Protective cover, circular, Accessories, with self-locking mechanism, for attaching to infrastructure charging sockets, GB/T, Type 2, GB/T 20234.2, IEC 62196-2, Front mounting, housing: black, Adhered "PHOENIX CONTACT" sticker

## Product description

Self-closing protective cover for infrastructure charging socket

## Your advantages

- Developed and produced in accordance with the IATF 16949 automotive standard and ISO 9001
- Individual branding, thanks to the use your own logo
- Reliable protection of your socket outlet from weather and vandalism

### Commercial data

Item number	1623888
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	XWBAFF
GTIN	4055626202464
Weight per piece (including packing)	190 g
Weight per piece (excluding packing)	180 g
Country of origin	CN



1623888

https://www.phoenixcontact.com/us/products/1623888

## Technical data

## Product properties

Design (Protective cover)	circular
Product type	Protective cover for Socket Outlet
Product family	CHARX connect basic
Application	for attaching to infrastructure charging sockets
Туре	Accessories
Design	with self-locking mechanism
Affixed logo	Adhered "PHOENIX CONTACT" sticker
Label	14.1 mm x 44.8 mm (customer logo on request)
Charging standard	GB/T
	Type 2
Charging mode	Mode 3, Case B

### **Dimensions**

### Protective cover

Dimensional drawing	2x 07.3 1
Width	76.6 mm
Height	76.6 mm
Depth	24.7 mm

### Bore dimensions

Dorc difficultions	
Dimensional drawing	
Width	60 mm
Height	60 mm

### Material specifications

Color (Housing)	black (9005)
Material (Housing)	Plastic
Flammability rating according to UL 94	V0 ()

### Environmental and real-life conditions



1623888

https://www.phoenixcontact.com/us/products/1623888

#### Ambient conditions

Degree of protection (Protective cover)	IP54 (plugged in)
Ambient temperature (operation)	-30 °C 50 °C
Ambient temperature (storage/transport)	-40 °C 80 °C

## Standards and regulations

### Standards

Standards/regulations	GB/T 20234.2
	IEC 62196-2

### Mounting

Mounting type Protective cover	Front mounting (rear screw connection)
Mounting type Infrastructure charging socket	right or left-sided installation
Mounting hole diameter	6.50 mm (ø)



1623888

https://www.phoenixcontact.com/us/products/1623888

## Classifications

UNSPSC 21.0

### **ECLASS**

ECLASS-11.0	27144792
ECLASS-12.0	27144792
ECLASS-13.0	27144792
ETIM	
ETIM 9.0	EC002884
UNSPSC	

39121500



1623888

https://www.phoenixcontact.com/us/products/1623888

## Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 10;
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com