

https://www.phoenixcontact.com/us/products/2202994



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Perfboard with GPIO connection incl. PTSM terminal blocks



Commercial data

	0000004
Item number	2202994
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AC10
Product key	ACHBAE
GTIN	4055626292618
Weight per piece (including packing)	30.2 g
Weight per piece (excluding packing)	30.33 g
Customs tariff number	85366990
Country of origin	DE



https://www.phoenixcontact.com/us/products/2202994



Set consists of

PSTD 0,65X0,65/40-2,54 - Female strip

2202992

https://www.phoenixcontact.com/us/products/2202992

Female strip for connecting an additional PCB or PCB with hole pattern to the GPIOs of the Raspberry Pi computer



PTSM 0,5/ 4-HH-2,5-THR WH R32 - PCB header

1814867

https://www.phoenixcontact.com/us/products/1814867



PCB headers, nominal cross section: 0.5 mm², color: signal white, nominal current: 6 A, rated voltage (III/2): 160 V, contact surface: Tin, contact connection type: Pin, number of potentials: 4, number of rows: 1, number of positions: 4, number of connections: 4, product range: PTSM 0,5/..-HH-THR WH, pitch: 2.5 mm, mounting: THR soldering, pin layout: Linear pinning, solder pin [P]: 2.1 mm, number of solder pins per potential: 1, plug-in system: COMBICON PTSM, Pin connector pattern alignment: Standard, locking: without, mounting: without, type of packaging: 32 mm wide tape



https://www.phoenixcontact.com/us/products/2202994



PTSM 0,5/4-P-2,5 WH - PCB connector

1704857

https://www.phoenixcontact.com/us/products/1704857



PCB connector, nominal cross section: 0.5 mm², color: white, nominal current: 6 A, rated voltage (III/2): 160 V, contact surface: Tin, contact connection type: Socket, number of potentials: 4, number of rows: 1, number of positions: 4, number of connections: 4, product range: PTSM 0,5/..-P WH, pitch: 2.5 mm, connection method: Push-in spring connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON PTSM, locking: without, mounting: without, type of packaging: packed in cardboard



https://www.phoenixcontact.com/us/products/2202994



Technical data

Product properties

Product type	Sample set
Housing series	BC
Pitch	2.54 mm
Housing type	DIN rail housing

Dimensions

Dist	0.54
Pitch	2.54 mm

Material specifications

Color	green/white
Flammability rating according to UL 94	V0
Housing material	FR 4-21



2202994

https://www.phoenixcontact.com/us/products/2202994

Classifications

ECLASS

	ECLASS-11.0	27182702		
	ECLASS-13.0	27260692		
ETIM				
	ETIM 9.0	EC001031		
UNSPSC				
	UNSPSC 21.0	31261500		



https://www.phoenixcontact.com/us/products/2202994



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com