

# PLC-VT/ACT - Feed-through terminal block



2295567

<https://www.phoenixcontact.com/us/products/2295567>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VARIOFACE feed-through terminal block (3-conductor screw connection), for PLC-INTERFACE actuator series

## Your advantages

- Can be combined with PLC-INTERFACE actuator series
- With LED as an option
- Signal path with two additional potential levels for free assignment (3-conductor connection)

## Commercial data

Item number	2295567
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	C421
Product key	CK21C3
Catalog page	Page 532 (C-5-2019)
GTIN	4017918821852
Weight per piece (including packing)	34.07 g
Weight per piece (excluding packing)	27.64 g
Customs tariff number	85369010
Country of origin	DE

# PLC-VT/ACT - Feed-through terminal block



2295567

<https://www.phoenixcontact.com/us/products/2295567>

## Technical data

### Notes

General	The necessary requirements for insulation (basic insulation or reinforced insulation) from adjacent modules (in DIN-rail direction) must be realized by applying suitable measures (e. g., partition plates).
General	Ensure that the supply voltage of the device has a common reference potential.
General	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.

### Product properties

Product type	Feed-through terminal block
Product family	PLC-INTERFACE

### Insulation characteristics

Insulation	Functional insulation
------------	-----------------------

### Insulation characteristics: Air clearances and creepage distances

Insulation	Functional insulation
Overvoltage category	III
Pollution degree	2

### Electrical properties

Operating voltage (AC/DC)	250 V AC/DC
Current (per branch)	≤ 6 A
Current (per connection terminal block with bridge shaft)	≤ 6 A

### Air clearances and creepage distances

Rated insulation voltage	300 V
Rated surge voltage	4 kV

### Connection data

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Number of positions	5
Conductor cross section rigid	0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>
Conductor cross section flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section AWG	24 ... 12

### Signaling

Status display present	No
------------------------	----

# PLC-VT/ACT - Feed-through terminal block



2295567

<https://www.phoenixcontact.com/us/products/2295567>

## Dimensions

### Item dimensions

Width	6.2 mm
Height	80 mm
Depth	92.5 mm

## Material specifications

Color	gray (RAL 7042)
Flammability rating according to UL 94	V0

## Environmental and real-life conditions

### Ambient conditions

Degree of protection (Module)	IP20
Degree of protection (Installation location)	≥ IP54
Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

## Approvals

### CE

Certificate	CE-compliant
-------------	--------------

### UKCA

Certificate	UKCA-compliant
-------------	----------------

### Shipbuilding approval

Certificate	TAE0000196
-------------	------------

### DNV GL data

Temperature	D
Humidity	A
Vibration	B/C
EMC	B
Enclosure	Required protection according to the Rules shall be provided upon installation on board

## EMC data

Low Voltage Directive	Conformance with Low Voltage Directive
Electromagnetic compatibility	Conformance with EMC directive

## Standards and regulations

### Air clearances and creepage distances

Standards/regulations	EN IEC 60664-1
-----------------------	----------------

## Mounting

# PLC-VT/ACT - Feed-through terminal block



2295567

<https://www.phoenixcontact.com/us/products/2295567>

Mounting type	DIN rail mounting
Assembly instructions	in rows with zero spacing
Mounting position	any

# PLC-VT/ACT - Feed-through terminal block



2295567

<https://www.phoenixcontact.com/us/products/2295567>

## Classifications

### ECLASS

ECLASS-11.0	27371692
ECLASS-12.0	27371692
ECLASS-13.0	27371692

### ETIM

ETIM 9.0	EC002586
----------	----------

### UNSPSC

UNSPSC 21.0	39122300
-------------	----------

# PLC-VT/ACT - Feed-through terminal block



2295567

<https://www.phoenixcontact.com/us/products/2295567>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)