

FLKM 14-PA-INLINE/32 - Front adapter




2302777

<https://www.phoenixcontact.com/us/products/2302777>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

VARIOFACE front adapter for Inline modules, for transferring 32 (4 x 8) digital signals.



Commercial data

Item number	2302777
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C421
Product key	CK2115
Catalog page	Page 486 (C-5-2019)
GTIN	4017918929466
Weight per piece (including packing)	69.2 g
Weight per piece (excluding packing)	44.67 g
Customs tariff number	85369010
Country of origin	DE

FLKM 14-PA-INLINE/32 - Front adapter



2302777

<https://www.phoenixcontact.com/us/products/2302777>

Technical data

Product properties

Product type	Front adapter
Product family	VARIOFACE

Insulation characteristics

Insulation	Functional insulation
------------	-----------------------

Insulation characteristics: Air clearances and creepage distances

Insulation	Functional insulation
Overvoltage category	II
Pollution degree	2

Electrical properties

Operating voltage (DC)	≤ 60 V DC
Current (per branch)	≤ 1 A

Air clearances and creepage distances

Rated insulation voltage	63 V
Rated surge voltage	0.6 kV (1.2/50 μs)

Supported controller PHOENIX CONTACT Inline

Suitable I/O card	IB IL 24 DI 32/HD-PAC
	IB IL 24 DO 32/HD-PAC
	IB IL 24 DI 32/HD-NPN-PAC

Connection data

Connection 1 (control level)

Connection method	Plug-in connection
Number of connections	1
Number of positions	32

Connection 2 (field level)

Connection in acc. with standard	IEC 60603-13
Connection method	IDC/FLK pin strip
Number of connections	4
Number of positions	14
Insertion/withdrawal cycles	> 50
Pitch	2.54 mm

Dimensions

Item dimensions

Width	44 mm
Height	66.5 mm

FLKM 14-PA-INLINE/32 - Front adapter



2302777

<https://www.phoenixcontact.com/us/products/2302777>

Depth	33.85 mm
-------	----------

Environmental and real-life conditions

Ambient conditions

Degree of protection (Module)	IP20
Degree of protection (Installation location)	≥ IP54
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 50 °C
Altitude	≤ 2000 m

Standards and regulations

Air clearances and creepage distances

Standards/regulations	EN IEC 60664-1
-----------------------	----------------

Mounting

Mounting type	Plug-in mounting
Mounting position	any

Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
---------	--

FLKM 14-PA-INLINE/32 - Front adapter



2302777

<https://www.phoenixcontact.com/us/products/2302777>

Classifications

ECLASS

ECLASS-11.0	27242292
ECLASS-12.0	27242292
ECLASS-13.0	27242292

ETIM

ETIM 9.0	EC002584
----------	----------

UNSPSC

UNSPSC 21.0	32151600
-------------	----------

FLKM 14-PA-INLINE/32 - Front adapter



2302777

<https://www.phoenixcontact.com/us/products/2302777>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com