

Touch panel - TP 3185W/P - 2403862

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Touch panel with 47.0 cm / 18.5" TFT-display (Projective-capacitive (PCAP)), 1366 x 768 pixel(s) (WXGA), 65536 colors, Arm® Cortex®-A8, 1000 MHz, 2x USB host 2.0, 1 x Ethernet (10/100 Mbps), RJ45, Windows® Embedded Compact 7 and user software: Visu+. (bus system: without)


Similar figure

Your advantages

- ✓ Robust and sturdy, thanks to glass front suitable for industrial use
- ✓ Fast response and display refresh, thanks to powerful processor
- ✓ Flexible connection to third-party systems by means of various drivers
- ✓ Integrated Visu+ visualization software
- ✓ Mobile system access with the Visu+ mobile app



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 363578
GTIN	4055626363578
Weight per Piece (excluding packing)	6,700.000 g
Custom tariff number	84714100
Country of origin	Germany

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Outer dimensions: width, height, depth	485 mm x 329 mm x 8 mm (Dimensions of the front plate)
--	--

Touch panel - TP 3185W/P - 2403862

Technical data

Dimensions

Installation dimensions: width, height, depth	475 mm x 311 mm x 53 mm (Installation cutout)
---	---

Display

Display type	47.0 cm / 18.5" TFT
Screen resolution	1366 x 768 Pixel(s) (WXGA)
Touch technology	Projective-capacitive (PCAP)
Brightness	240 cd/m², typical (adjustable)
Backlighting	LED
Display backlight MTBF	50000 h
Colors	65536 colors
Reading angle left	85 °
Reading angle right	85 °
Reading angle top	80 °
Reading angle bottom	80 °

Computer data

Processor	Arm® Cortex®-A8, 1000 MHz
Operating system	Windows® Embedded Compact 7
User software	Visu+
RAM	512 MB LPDDR RAM
Mass storage	NAND-Flash, 1 GB
Network	1 x Ethernet (10/100 Mbps), RJ45
Interfaces	2x USB Host 2.0
Bus system	without
Slots	1x SD
Realtime clock	Yes (battery-backed)
Service life of battery	5 years (typical)

General

Material front plate	Aluminum (natural anodized)
Housing material	Steel sheet, zinc-plated
Mounting type	Front installation
Weight	5600 g

Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
	NEMA 4X
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C

Touch panel - TP 3185W/P - 2403862

Technical data

Ambient conditions

Permissible humidity (operation)	20 % ... 85 % (non-condensing)
Permissible humidity (storage/transport)	20 % ... 85 % (non-condensing)
Vibration (operation)	DIN EN 60068-2-6
Shock	DIN EN 60068-2-27

Device supply

Supply voltage	24 V DC
Supply voltage range	18 V DC ... 30 V DC
Typical current consumption	1.2 A
Power consumption	typ. 28.8 W
Power supply unit	24 V DC \pm 20 %

Standards and Regulations

Shock	DIN EN 60068-2-27
Vibration (operation)	DIN EN 60068-2-6

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 15;
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 10.0.1	27330201
eCl@ss 11.0	27330201
eCl@ss 4.0	27330200
eCl@ss 4.1	27330200
eCl@ss 5.0	27330200
eCl@ss 5.1	27330200
eCl@ss 6.0	27242300
eCl@ss 7.0	27242302
eCl@ss 9.0	27330201

ETIM

ETIM 4.0	EC001412
ETIM 6.0	EC001412
ETIM 7.0	EC001412

Touch panel - TP 3185W/P - 2403862

Classifications

UNSPSC

UNSPSC 13.2	43211904
UNSPSC 18.0	43211904
UNSPSC 19.0	43211904
UNSPSC 20.0	43211904
UNSPSC 21.0	43211904

Approvals


Approvals

Approvals


UL Listed / cUL Listed / cULus Listed

Ex Approvals

Approval details

UL Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 205795
-----------	---	---	---------------

cUL Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 205795
------------	---	---	---------------

cULus Listed			
--------------	---	--	--