

IB IL TEMP 8 UTH/RTD-PAC - Temperature module



2701000

<https://www.phoenixcontact.com/us/products/2701000>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Inline analog input terminal, complete with accessories (connector and marking field), 8 channels, TC (thermocouple), RTD (resistance temperature detector), 2 and 3-conductor connection technology

Product description

The terminal is designed for use within an Inline station. This terminal provides an 8-channel input module with two linear resistance ranges for resistance temperature detectors, and a voltage range for thermocouples. This terminal supports, for example:– Platinum and nickel sensors, e.g. , Pt 100, Pt 1000, Ni 100, and Ni 1000 according to EN 60751 and DIN 43760– All standard thermocouples according to EN 60584-1 and DIN 43710 Communication is via the parameter channel (PCP) or via the process data.

Your advantages

- 8 temperature sensor inputs
- 3-conductor connection for resistance temperature detectors (Pt 100, Ni 100, Pt 1000, Ni 1000, and others)
- 2-conductor connection for thermocouples
- Internal and external detection and compensation of cold junction temperature (configurable)
- Individual current input, 1 A for total current transformer for heating current monitoring
- Scan time: 20 ms (for all channels)
- Maximum 50 Hz/60 Hz suppression
- High precision and noise immunity
- Temperature stability
- High-resolution temperature, voltage, and resistance measurement
- Resistance values (R0) can be preset separately by means of parameterization
- Channels are parameterized independently of one another
- Diagnostic and status indicators
- Channel scout functionality, for optical channel identification during startup

Commercial data

Item number	2701000
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DR01
Product key	DRI143
Catalog page	Page 140 (C-6-2019)
GTIN	4046356673594
Weight per piece (including packing)	234 g
Weight per piece (excluding packing)	234 g

IB IL TEMP 8 UTH/RTD-PAC - Temperature module



2701000

<https://www.phoenixcontact.com/us/products/2701000>

Customs tariff number	85389099
Country of origin	DE

IB IL TEMP 8 UTH/RTD-PAC - Temperature module



2701000

<https://www.phoenixcontact.com/us/products/2701000>

Technical data

Dimensions

Dimensional drawing	
Width	48.8 mm
Height	119.8 mm
Depth	71.5 mm

Interfaces

Inline local bus

Connection method	Inline data jumper
Transmission speed	500 kbps
Transmission physics	Copper

System properties

Module

ID code (dec.)	220
ID code (hex)	DC
Length code (hex)	0A
Length code (dec)	10
Process data channel	160 bit
Input address area	20 Byte
Output address area	20 Byte
Register length	192 bit
Required parameter data	25 Byte
Required configuration data	5 Byte

Input data

Analog

Input name	Analog RTD inputs
Description of the input	Temperature sensor inputs
Number of inputs	8
Connection method	Spring-cage connection
Connection technology	2-, 3-conductor
A/D converter resolution	16 bit
Sensor types (RTD) that can be used	Pt, Ni sensors, linear resistors

IB IL TEMP 8 UTH/RTD-PAC - Temperature module



2701000

<https://www.phoenixcontact.com/us/products/2701000>

Sensor types that can be used (TC)	B, C, E, J, K, L, N, R, S, T, U, mV input
Data formats	IB IL, S7-compatible
Measuring principle	Successive approximation
Measured value representation	16 bits (15 bits + sign bit)
Process data update	20 ms (with filter time of 20 ms or 100 ms) 100 ms (with filter time of 400 ms or 1600 ms)

Product properties

Type	modular
Product type	I/O component
Product family	Inline
Scope of delivery	including Inline connectors and marking fields
Operating mode	Process data mode with 10 words, PCP with 2 words

Insulation characteristics

Overvoltage category	II (IEC 60664-1, EN 60664-1)
Pollution degree	2 (IEC 60664-1, EN 60664-1)

Electrical properties

Potentials

Power consumption	typ. 1.15 W
-------------------	-------------

Potentials: Communications power (U_L)

Supply voltage	7.5 V DC (via voltage jumper)
Current draw	max. 100 mA typ. 90 mA

Potentials: Supply of analog modules (U_{ANA})

Supply voltage	24 V DC (via voltage jumper)
Supply voltage range	19.2 V DC ... 30 V DC (including all tolerances, including ripple)
Current draw	typ. 24 mA

Electrical isolation/isolation of the voltage ranges

Test voltage: 5 V supply, incoming remote bus/7.5 V supply (bus logics)	500 V AC, 50 Hz, 1 min.
Test voltage: 5 V supply, outgoing remote bus/7.5 V supply (bus logics)	500 V AC, 50 Hz, 1 min.
Test voltage: 7.5 V supply (bus logic), 24 V supply U_{ANA} / I/O	500 V AC, 50 Hz, 1 min.

Connection data

Connection technology

Connection name	Inline connector
-----------------	------------------

Conductor connection

Connection method	Spring-cage connection
Conductor cross section rigid	0.08 mm ² ... 1.5 mm ²

IB IL TEMP 8 UTH/RTD-PAC - Temperature module



2701000

<https://www.phoenixcontact.com/us/products/2701000>

Conductor cross section flexible	0.08 mm ² ... 1.5 mm ²
Conductor cross section AWG	28 ... 16
Stripping length	8 mm

Inline connector

Connection method	Spring-cage connection
Conductor cross section, rigid	0.08 mm ² ... 1.5 mm ²
Conductor cross section, flexible	0.08 mm ² ... 1.5 mm ²
Conductor cross section AWG	28 ... 16
Stripping length	8 mm

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-25 °C ... 60 °C
Degree of protection	IP20
Air pressure (operation)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)

Standards and regulations

Protection class	III (IEC 61140, EN 61140, VDE 0140-1)
------------------	---------------------------------------

Mounting

Mounting type	DIN rail mounting
---------------	-------------------

IB IL TEMP 8 UTH/RTD-PAC - Temperature module



2701000

<https://www.phoenixcontact.com/us/products/2701000>

Classifications

ECLASS

ECLASS-11.0	27242601
ECLASS-12.0	27242601
ECLASS-13.0	27242601

ETIM

ETIM 9.0	EC001596
----------	----------

UNSPSC

UNSPSC 21.0	32151600
-------------	----------

IB IL TEMP 8 UTH/RTD-PAC - Temperature module



2701000

<https://www.phoenixcontact.com/us/products/2701000>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com