

PLD M 260 W-75/95 790/D70 - LED machine light



2702488

<https://www.phoenixcontact.com/us/products/2702488>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



LED machine light, 24 V DC, emission angle (vertical/Horizontal): 75 °/95 °, length: 790 mm, diameter: 70 mm, degree of protection: IP67, can be swiveled, resistant to coolants and lubricants

Product description

This LED machine light is designed to provide illumination inside or on machinery. You can use the light in harsh environments. This is possible thanks to the following properties: - High type of protection - Resistance to common cooling agents and lubricants - Resistance to vibrations and shock - 4 mm-thick safety glass The 70 mm diameter enables easy replacement of conventional tube lights. Mounting is by means of holders or brackets (neither of which are supplied as standard) in which the light can swivel and the lighting can therefore be optimally aligned.

Your advantages

- Easy mechanical replacement of traditional tube lights (retrofit), thanks to 70 mm diameter
- Plug-in supply line enables free choice of the cable length as well as quick and easy installation
- Focused illumination, thanks to swivel action
- IP67 protection and resistance to cooling agents and lubricants enables use in machine tools
- Can be used at high temperatures and can be subjected to strong vibrations and shocks
- Safety glass enables use even in environments with potential mechanical strain
- ETL approval permits use on the North American market
- Particularly economical thanks to energy-efficient LED technology and an LED service life of at least 60,000 h

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 2702488 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | DR08 |
| Product key | DRL222 |
| Catalog page | Page 507 (C-6-2019) |
| GTIN | 4055626216782 |
| Weight per piece (including packing) | 3,030 g |
| Weight per piece (excluding packing) | 2,500 g |
| Customs tariff number | 94054239 |
| Country of origin | DE |

PLD M 260 W-75/95 790/D70 - LED machine light



2702488

<https://www.phoenixcontact.com/us/products/2702488>

Technical data

Notes

| | |
|---------|--|
| General | The PLD M-ME MC/D70 mounting holder (Item No. 2702493) or the PLD M-ME MB/D70 mounting bracket (Item No. 2702494) is required in order to mount the light. |
|---------|--|

Product properties

| | |
|--------------------|---|
| Product type | Machine light |
| Mounting position | any |
| Application | Machine tool |
| Special properties | can be swiveled with mounting accessories resistant to coolants and lubricants |

Electrical properties

Supply: Module electronics

| | |
|-------------------------------------|--|
| Connection method | M12 connector (A-coded) |
| Number of positions | 4 |
| Permissible conductor cross section | min. 0.34 mm ² |
| Supply voltage | 24 V DC |
| Supply voltage range | 18 V DC ... 30 V DC |
| Current consumption | typ. 1.25 A (at 24 V DC) |
| Power consumption | approx. 30 W (at 24 V DC) |
| Protective circuit | Surge protection; Varistor and suppressor diode, 36 V DC Reverse polarity protection; Polarity protection diode |

Connection data

| | |
|-------------------|-------------------------|
| Connection method | M12 connector (A-coded) |
|-------------------|-------------------------|

Signaling

Light properties

| | |
|----------------------------------|--|
| Source of light type | LED |
| Number of LEDs | 60 |
| Service life, lighting appliance | 60000 h (L70) |
| Color temperature | 5000 K ±8 % |
| Color rendering index | 85 |
| Luminous flux | approx. 2300 lm (Net luminous flux) |
| Luminous efficacy | approx. 77 lm/W |
| Illumination | max. 1056 lx (Distance of 1 m) min. 518 lx (Distance of 1 m over 1 m ² area) |
| Average illumination | 814 lx (Distance of 1 m over 1 m ² area) |
| Emission angle | 75 ° (C0-C180) 95 ° (C90-C270) |

PLD M 260 W-75/95 790/D70 - LED machine light




2702488

<https://www.phoenixcontact.com/us/products/2702488>

| | |
|-------------------------|--|
| Ordinance | Delegated Regulation (EU) 2019/2015 |
| Energy efficiency class | D (1 light source) |
| | E (1 light source) |
| Note | This product contains an energy efficiency class D light source. |
| | This product contains an energy efficiency class E light source. |

Dimensions

| | |
|---------------------|--|
| Dimensional drawing |  |
| Width | 70 mm |
| Height | 58 mm |
| Length | 790 mm |
| Diameter | 70 mm |
| Note on dimensions | Length without M12 flush-type connector |

Material specifications

| | |
|--------------|--|
| Color | aluminum color |
| Material () | Anodized aluminum (Light housing) |
| | Single-pane safety glass (ESG, thermally toughened float glass) (Pane) |

Environmental and real-life conditions

Ambient conditions

| | |
|--|-----------------------|
| Ambient temperature (operation) | 0 °C ... 45 °C |
| Degree of protection | IP67 |
| Air pressure (operation) | 69 kPa ... 102 kPa |
| Air pressure (storage/transport) | 69 kPa ... 102 kPa |
| Ambient temperature (storage/transport) | -20 °C ... 75 °C |
| Permissible humidity (operation) | 95 % (non-condensing) |
| Permissible humidity (storage/transport) | 95 % (non-condensing) |

Standards and regulations

| | |
|------------------|---------------------------------------|
| Protection class | III (IEC 61140, EN 61140, VDE 0140-1) |
|------------------|---------------------------------------|

Mounting

| | |
|-----------------------|--|
| Mounting type | Screw mounting |
| Assembly instructions | Mounting with mounting holders or mounting brackets, please observe the notes in the package slip. |
| Mounting position | any |

PLD M 260 W-75/95 790/D70 - LED machine light



2702488

<https://www.phoenixcontact.com/us/products/2702488>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27110345 |
| ECLASS-12.0 | 27110345 |
| ECLASS-13.0 | 27110345 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC000348 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 32151500 |
|-------------|----------|

PLD M 260 W-75/95 790/D70 - LED machine light



2702488

<https://www.phoenixcontact.com/us/products/2702488>

Environmental product compliance

| | |
|------------|--|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com