

# PLT-SEC-T3-3S-230-P - Type 3 surge protection plug



2905236

<https://www.phoenixcontact.com/us/products/2905236>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Replacement plug for type 3 device protection from the PLUGTRAB SEC T3 3S product range.  
230 V nominal voltage.

## Your advantages

- Surge protection family for universal use with optimum energy coordination from the lightning current arrester to the device protection
- Easy to maintain due to consistently pluggable protection modules
- Excellent level of information provided by mechanical/visual status indicator and remote indication contact
- Your preferred connection technology can be selected as both screw connection and Push-in connection are available
- Optimal additional protection of the industrial power supply for a longer service life and increased availability of the system

## Commercial data

Item number	2905236
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	CL19
Product key	CL14A1
Catalog page	Page 82 (C-4-2019)
GTIN	4046356939751
Weight per piece (including packing)	80.9 g
Weight per piece (excluding packing)	80.9 g
Customs tariff number	85363090
Country of origin	DE

# PLT-SEC-T3-3S-230-P - Type 3 surge protection plug



2905236

<https://www.phoenixcontact.com/us/products/2905236>

## Technical data

### Product properties

IEC power supply system	TN-S
	TT
Type	Male
Product type	Replacement plug
Product family	SEC Family
Number of positions	4
Surge protection fault message	optical


### Insulation characteristics

Overvoltage category	III
Pollution degree	2
IEC test classification	III
	T3
EN type	T3

### Connection data

Connection method	pluggable
-------------------	-----------

### Dimensions

Dimensional drawing	
Width	35.2 mm
Height	44.8 mm
Depth	60.9 mm
Horizontal pitch	2 Div.

### Material specifications

Color	light grey (RAL 7035)
Flammability rating according to UL 94	V-0
CTI value of material	600
Insulating material	PA 6.6-FR 20% GF
	PA 6.6-FR
Material group	I
Housing material	PA 6.6-FR 20 % GF
	PA 6.6-FR

### Protective circuit

	L-N
--	-----

# PLT-SEC-T3-3S-230-P - Type 3 surge protection plug



2905236

<https://www.phoenixcontact.com/us/products/2905236>

Mode of protection	L-PE
	N-PE
Direction of action	3L-N & N-PE
Nominal voltage $U_N$	230/400 V AC (TN-S)
	230/400 V AC (TT - only in use with RCD)
Nominal frequency $f_N$	50 Hz (60 Hz)
Maximum continuous voltage $U_C$	264 V AC
Residual current $I_{PE}$	$\leq 5 \mu A$
Standby power consumption $P_C$	$\leq 2.00$ VA (at $U_{REF}$ )
	$\leq 2.20$ VA (at $U_C$ )
Reference test voltage $U_{REF}$	255.00 V AC
Nominal discharge current $I_n$ (8/20) $\mu s$	3 kA
Combination wave $U_{OC}$	6 kV
Voltage protection level $U_p$ (L-N)	$\leq 1.4$ kV
Voltage protection level $U_p$ (L-PE)	$\leq 1.5$ kV
Voltage protection level $U_p$ (N-PE)	$\leq 1.5$ kV
TOV behavior at $U_T$ (L-N)	440 V AC (5 s / withstand mode)
	440 V AC (120 min / withstand mode)
TOV behavior at $U_T$ (L-PE)	440 V AC (5 s / withstand mode)
	440 V AC (120 min / withstand mode)
	1455 V AC (200 ms / safe failure mode)
TOV behavior at $U_T$ (N-PE)	1200 V AC (200 ms / safe failure mode)
Response time $t_A$ (L-N)	$\leq 25$ ns
Response time $t_A$ (L-PE)	$\leq 100$ ns
Response time $t_A$ (N-PE)	$\leq 100$ ns
Short-circuit current rating $I_{SCCR}$	1.5 kA AC

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Altitude	$\leq 2000$ m (amsl)
Permissible humidity (operation)	5 % ... 95 %
Shock (operation)	30g (Half-sine / 11 ms / $3x \pm X, \pm Y, \pm Z$ )
Vibration (operation)	5g (10 ... 150 Hz/20 cycles/axis/X, Y, Z)

## Standards and regulations

Standards/specifications	IEC 61643-11
Note	2011

### EN 61643-11

Standards/specifications	EN 61643-11
Note	2012

# PLT-SEC-T3-3S-230-P - Type 3 surge protection plug



2905236

<https://www.phoenixcontact.com/us/products/2905236>

## Mounting

Mounting type
---------------

on base element
-----------------

# PLT-SEC-T3-3S-230-P - Type 3 surge protection plug



2905236

<https://www.phoenixcontact.com/us/products/2905236>

## Classifications

### ECLASS

ECLASS-11.0	27130890
ECLASS-13.0	27171292

### ETIM

ETIM 9.0	EC002496
----------	----------

### UNSPSC

UNSPSC 21.0	39121600
-------------	----------

# PLT-SEC-T3-3S-230-P - Type 3 surge protection plug



2905236

<https://www.phoenixcontact.com/us/products/2905236>

## Environmental product compliance

REACH SVHC	Lead 7439-92-1
	Dechlorane Plus
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)