

VAL-SEC-T2-N/PE-175-P - Type 2 surge protection plug



2905356

<https://www.phoenixcontact.com/us/products/2905356>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Replacement plug for surge arresters from the VALVETRAB SEC product range for the N-PE path.

Your advantages

- Surge protection family for universal use with optimum energy coordination from the lightning current arrester to the device protection
- Easy to maintain due to consistently pluggable protection modules
- Excellent level of information provided by mechanical/visual status indicator and remote indication contact
- More space in the control cabinet due to the narrow overall width of just 12 mm per position and use without separate backup fuse up to 315 A gG

Commercial data

| | |
|--------------------------------------|--------------------|
| Item number | 2905356 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | CL01 |
| Product key | CL1351 |
| Catalog page | Page 56 (C-4-2019) |
| GTIN | 4046356948227 |
| Weight per piece (including packing) | 50.8 g |
| Weight per piece (excluding packing) | 49.3 g |
| Customs tariff number | 85363090 |
| Country of origin | DE |

VAL-SEC-T2-N/PE-175-P - Type 2 surge protection plug

2905356

<https://www.phoenixcontact.com/us/products/2905356>

Technical data

Product properties

| | |
|--------------------------------|------------------|
| IEC test classification | II |
| | T2 |
| EN type | T2 |
| IEC power supply system | TN |
| | TT |
| Type | Male |
| Product type | Replacement plug |
| Product family | SEC Family |
| Number of positions | 1 |
| Surge protection fault message | optical |

Insulation characteristics

| | |
|----------------------|-----|
| Overvoltage category | III |
| Pollution degree | 2 |

Electrical properties

| | |
|-------------------------|---------------|
| Nominal frequency f_N | 50 Hz (60 Hz) |
|-------------------------|---------------|

Connection data

| | |
|-------------------|-----------|
| Connection method | pluggable |
|-------------------|-----------|

Dimensions

| | |
|---------------------|--|
| Dimensional drawing |  |
| Width | 11.7 mm |
| Height | 46.4 mm |
| Depth | 59.4 mm |
| Horizontal pitch | 0.6 Div. |

Material specifications

| | |
|--|-----------------------|
| Color | light grey (RAL 7035) |
| | gray (RAL 7042) |
| Flammability rating according to UL 94 | V-0 |
| CTI value of material | 600 |
| Insulating material | PA6.6-FR 20% GF |
| | PBT-FR |
| Material group | I |

VAL-SEC-T2-N/PE-175-P - Type 2 surge protection plug



2905356

<https://www.phoenixcontact.com/us/products/2905356>

| | |
|------------------|-------------------|
| Housing material | PA 6.6-FR 20 % GF |
| | PBT-FR |

Protective circuit

| | |
|--|-------------------------------------|
| Mode of protection | N-PE |
| Direction of action | N-PE |
| Nominal voltage U_N | 120 V AC (TN - only N-PE) |
| | 120 V AC (TT - only N-PE) |
| Nominal frequency f_N | 50 Hz (60 Hz) |
| Maximum continuous voltage U_C | 150 V AC |
| Residual current I_{PE} | $\leq 1 \mu\text{A}$ |
| Nominal discharge current I_n (8/20) μs | 20 kA |
| Maximum discharge current I_{max} (8/20) μs | 40 kA |
| Follow current interrupt rating I_{fi} | 100 A (150 V AC) |
| Voltage protection level U_p | $\leq 0.95 \text{ kV}$ |
| Residual voltage U_{res} | $\leq 0.4 \text{ kV}$ (at I_n) |
| | $\leq 0.4 \text{ kV}$ (at 10 kA) |
| | $\leq 0.4 \text{ kV}$ (at 5 kA) |
| | $\leq 0.4 \text{ kV}$ (at 4 kA) |
| | $\leq 0.4 \text{ kV}$ (at 2 kA) |
| Front of wave sparkover voltage at 6 kV (1.2/50) μs | $\leq 0.95 \text{ kV}$ |
| TOV behavior at U_T | 1200 V AC (200 ms / withstand mode) |
| Response time t_A | $\leq 100 \text{ ns}$ |

Environmental and real-life conditions

Ambient conditions

| | |
|---|---|
| Degree of protection | IP20 |
| Ambient temperature (operation) | -40 °C ... 80 °C |
| Ambient temperature (storage/transport) | -40 °C ... 80 °C |
| Altitude | $\leq 2000 \text{ m}$ (amsl) |
| Permissible humidity (operation) | 5 % ... 95 % |
| Shock (operation) | 30g (Half-sine / 11 ms / 3x $\pm X$, $\pm Y$, $\pm Z$) |
| Vibration (operation) | 5g (10 ... 500 Hz / 2.5 h / X, Y, Z) |

Approvals

UL specifications

| | |
|---|------------------|
| Maximum continuous operating voltage MCOV (N-G) | 150 V AC |
| Nominal discharge current I_n (N-G) | 20 kA |
| Mode of protection | N-G |
| Power distribution system | Single phase |
| Nominal frequency | 50/60 Hz |
| Measured limiting voltage MLV (N-G) | 560 V |
| Follow current (L-G) | 200 A (150 V AC) |

VAL-SEC-T2-N/PE-175-P - Type 2 surge protection plug



2905356

<https://www.phoenixcontact.com/us/products/2905356>

| | |
|----------|-----|
| SPD Type | 4CA |
|----------|-----|

Standards and regulations

| | |
|--------------------------|--------------|
| Standards/specifications | IEC 61643-11 |
| Note | 2011 |

EN 61643-11

| | |
|--------------------------|-------------|
| Standards/specifications | EN 61643-11 |
| Note | 2012 |

Mounting

| | |
|---------------|-----------------|
| Mounting type | on base element |
|---------------|-----------------|

VAL-SEC-T2-N/PE-175-P - Type 2 surge protection plug



2905356

<https://www.phoenixcontact.com/us/products/2905356>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27130890 |
| ECLASS-13.0 | 27171292 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC002496 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121600 |
|-------------|----------|

VAL-SEC-T2-N/PE-175-P - Type 2 surge protection plug



2905356

<https://www.phoenixcontact.com/us/products/2905356>

Environmental product compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com