

VAL-MB-T2 1500DC-PV/2+V-FM - Type 2 surge arrester



2905646

<https://www.phoenixcontact.com/us/products/2905646>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Surge protective device for 2-pos. isolated and grounded 1,500 V DC PV voltage systems, for DIN rail mounting, with remote indication contact, temperature-monitored protective elements, status message on the module.

Your advantages

- Space-saving installation, thanks to the compact design
- Double terminal block for safe and easy equipotential bonding connection
- Screw shafts with raised domes to ensure safe working
- Main connections with extended insertion funnels for increased resistance to creepage
- Visual display for checking the status directly on the device
- Plug-in signal connection for remote status signaling

Commercial data

Item number	2905646
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	CL1341
Catalog page	Page 72 (C-4-2019)
GTIN	4046356984195
Weight per piece (including packing)	389.4 g
Weight per piece (excluding packing)	389.4 g
Country of origin	DE

VAL-MB-T2 1500DC-PV/2+V-FM - Type 2 surge arrester



2905646

<https://www.phoenixcontact.com/us/products/2905646>

Technical data

Notes

General

Note	The product is also suitable for use in photovoltaic systems with max. short-circuit current $I_{SCPV} = 15 \text{ kA}$ (in accordance with EN 50539-11: 2013).
------	---

Product properties

IEC test classification	PV II PV T2
EN type	T2
IEC power supply system	DC
Type	DIN rail module, one-piece
Product type	PV arrester
Product family	VALVETRAB MB
Installation location	Interior
Installation location of the disconnect device	Internal
Accessibility	Accessible
Connection configuration	Y configuration
SPD failure behavior	OCFM (Open-Circuit Failure Mode)
Surge protection fault message	Optical, remote indicator contact

Insulation characteristics

Pollution degree	2
------------------	---

Electrical properties

Indicator/remote signaling

Connection name	Remote fault indicator contact
Switching function	Changeover contact
Operating voltage	5 V AC ... 250 V AC 5 V DC ... 30 V DC
Operating current	5 mA AC ... 1.5 A AC 5 mA DC ... 1 A DC

Connection data

Connection method	Screw connection
Screw thread	M5
Tightening torque	3 Nm
Stripping length	16 mm
Conductor cross section flexible	2.5 mm ² ... 35 mm ²
Conductor cross section AWG	14 ... 2

Remote fault indicator contact

VAL-MB-T2 1500DC-PV/2+V-FM - Type 2 surge arrester



2905646

<https://www.phoenixcontact.com/us/products/2905646>

Connection method	Screw connection
Screw thread	M2
Tightening torque	0.25 Nm
Stripping length	7 mm
Conductor cross section flexible	0.14 mm ² ... 1.5 mm ²
Conductor cross section rigid	0.14 mm ² ... 1.5 mm ²
Conductor cross section AWG	28 ... 16

Dimensions

Dimensional drawing	
Width	71.2 mm
Height	120 mm
Depth	65.5 mm (incl. DIN rail 7.5 mm)
Horizontal pitch	4 Div.

Material specifications

Color	gray (RAL 7042)
	gray (RAL 7042)
Flammability rating according to UL 94	V-0
Insulating material	PA 6.6
	PBT
Housing material	PA 6.6

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

Protective circuit

Mode of protection	(L+) - (L-)
	(L+) - PE
	(L-) - PE
Direction of action	(L+)-PE & (L-)-PE & (L+)-(L-)
Rated load current I_L	50 A
Residual current I_{PE}	$\leq 55 \mu\text{A DC}$
	$\leq 430 \mu\text{A AC}$
Standby power consumption P_C	$\leq 85.00 \text{ mVA}$
Nominal discharge current I_n (8/20) μs	20 kA
Maximum discharge current I_{max} (8/20) μs	40 kA
Total discharge current I_{total} (8/20) μs	40 kA
Voltage protection level U_p	$\leq 4.5 \text{ kV}$
	$\leq 4.5 \text{ kV (at } I_n)$

VAL-MB-T2 1500DC-PV/2+V-FM - Type 2 surge arrester



2905646

<https://www.phoenixcontact.com/us/products/2905646>

Residual voltage U_{res}	≤ 3.3 kV (at 3 kA)
	≤ 3.6 kV (at 6.25 kA)
	≤ 3.8 kV (at 10 kA)
	≤ 4.2 kV (at 15 kA)
	≤ 5.4 kV (at 40 kA)
Response time t_A	≤ 25 ns

PV protective circuit

Connection configuration	Y configuration
SPD failure behavior	OCFM (Open-Circuit Failure Mode)

Protective circuit DC voltage side (DC)

Open circuit voltage U_{OCSTC}	≤ 1250 V DC
Maximum discharge current I_{max} (8/20) μ s	40 kA
Response time t_A	≤ 25 ns
Total discharge current I_{total} (8/20) μ s	40 kA
Insulation resistance R_{iso}	> 5 G Ω (at 500 V DC)
Nominal discharge current I_n (8/20) μ s	20 kA
Rated load current I_L	50 A
Continuous operating current I_{CPV}	< 55 μ A
Maximum continuous operating voltage U_{CPV}	1500 V DC
Short-circuit current rating I_{SCPV}	2000 A
Residual voltage U_{res}	≤ 4.5 kV (at I_n)
	≤ 3.3 kV (at 3 kA)
	≤ 3.6 kV (at 6.25 kA)
	≤ 3.8 kV (at 10 kA)
	≤ 4.2 kV (at 15 kA)
Residual current I_{PE}	≤ 55 μ A DC
	≤ 430 μ A AC
Voltage protection level U_p	≤ 4.5 kV
Standby power consumption P_C	≤ 85.00 mVA

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20 (only when all terminal points are used)
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 6000 m (amsl)
Permissible humidity (operation)	5 % ... 95 %
Shock (operation)	50g (Half-sine / 11 ms / 3x \pm X, \pm Y, \pm Z)
Vibration (operation)	5g (5 - 500 Hz/2.5 h/X, Y, Z)

Standards and regulations

Standards/specifications	EN 61643-31
--------------------------	-------------

VAL-MB-T2 1500DC-PV/2+V-FM - Type 2 surge arrester



2905646

<https://www.phoenixcontact.com/us/products/2905646>

Note	2019
Standards/specifications	IEC 61643-31
Note	2018

Mounting

Mounting type	DIN rail: 35 mm
---------------	-----------------

VAL-MB-T2 1500DC-PV/2+V-FM - Type 2 surge arrester



2905646

<https://www.phoenixcontact.com/us/products/2905646>

Classifications

ECLASS

ECLASS-11.0	27130805
ECLASS-13.0	27171402

ETIM

ETIM 9.0	EC000941
----------	----------

UNSPSC

UNSPSC 21.0	39121600
-------------	----------

VAL-MB-T2 1500DC-PV/2+V-FM - Type 2 surge arrester



2905646

<https://www.phoenixcontact.com/us/products/2905646>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com