

VAL-SEC-T2-2+0-120DC-FM - Type 2 surge arrester



2907874

<https://www.phoenixcontact.com/us/products/2907874>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Pluggable surge protective device, in accordance with Type 2/Class II, for DC power sources with linear operating characteristics, with remote indication contact.

Your advantages

- Surge protection family for universal use with optimum energy coordination from the lightning current arrester to the device protection
- Easy to maintain due to consistently pluggable protection modules
- Excellent level of information provided by mechanical/visual status indicator and remote indication contact
- More space in the control cabinet due to the narrow overall width of just 12 mm per position
- Extremely narrow design, just 12 mm per position
- Varistor arrester with a low leakage current

Commercial data

| | |
|--------------------------------------|--------------------|
| Item number | 2907874 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | CL01 |
| Product key | CL1353 |
| Catalog page | Page 58 (C-4-2019) |
| GTIN | 4055626244594 |
| Weight per piece (including packing) | 214.3 g |
| Weight per piece (excluding packing) | 209.6 g |
| Customs tariff number | 85363090 |
| Country of origin | DE |

VAL-SEC-T2-2+0-120DC-FM - Type 2 surge arrester



2907874

<https://www.phoenixcontact.com/us/products/2907874>

Technical data

Product properties

| | |
|--------------------------------|---|
| IEC test classification | II |
| | T2 |
| EN type | T2 |
| IEC power supply system | DC |
| Type | DIN rail module, two-section, divisible |
| Product type | Surge arrester |
| Product family | SEC Family |
| Number of positions | 2 |
| Surge protection fault message | Optical, remote indicator contact |

Insulation characteristics

| | |
|----------------------|-----|
| Overvoltage category | III |
| Pollution degree | 2 |

Electrical properties

| | |
|-----------------------|-----------------------|
| Nominal voltage U_N | 100 V DC ... 120 V DC |
|-----------------------|-----------------------|

Indicator/remote signaling

| | |
|--------------------|---|
| Connection name | Remote fault indicator contact |
| Switching function | Changeover contact |
| Operating voltage | 5 V AC ... 250 V AC (Altitude \leq 2000 m (amsl)) |
| | 5 V AC ... 150 V AC (Altitude $>$ 2000 m (amsl)) |
| | 125 V DC (200 mA DC) |
| Operating current | 5 mA AC ... 1 A AC |
| | 1 A DC (30 V DC) |

Connection data

| | |
|----------------------------------|--|
| Connection method | Screw connection |
| Screw thread | M5 |
| Tightening torque | 4.5 Nm |
| Stripping length | 16 mm |
| Conductor cross section flexible | 2.5 mm ² ... 16 mm ² |
| Conductor cross section rigid | 2.5 mm ² ... 25 mm ² |
| Conductor cross section AWG | 12 ... 4 |
| Connection method | Fork-type cable lug |
| Conductor cross section flexible | 1.5 mm ² ... 6 mm ² |

Remote fault indicator contact

| | |
|-------------------|---------------------------------------|
| Connection method | Plug-in/screw connection via COMBICON |
| Screw thread | M2 |
| Tightening torque | 0.25 Nm |
| Stripping length | 7 mm |

VAL-SEC-T2-2+0-120DC-FM - Type 2 surge arrester



2907874

<https://www.phoenixcontact.com/us/products/2907874>

| | |
|----------------------------------|--|
| Conductor cross section flexible | 0.14 mm ² ... 1.5 mm ² |
| Conductor cross section rigid | 0.14 mm ² ... 1.5 mm ² |
| Conductor cross section AWG | 28 ... 16 |

Dimensions

| | |
|---------------------|---------------------------------|
| Dimensional drawing | |
| Width | 25.4 mm |
| Height | 97.9 mm |
| Depth | 74.5 mm (incl. DIN rail 7.5 mm) |
| Horizontal pitch | 1.4 Div. |

Material specifications

| | |
|--|-----------------------------|
| Color (Male connector) | light grey (RAL 7035) |
| Color (Base element) | gray (RAL 7042) |
| Flammability rating according to UL 94 | V-0 |
| CTI value of material | 600 |
| Insulating material | PA6.6-FR 20% GF PBT-FR |
| Material group | I |
| Housing material | PA 6.6-FR 20 % GF PBT-FR |

Protective circuit

| | |
|---|---|
| Mode of protection | (DC+) - (DC-) (DC+/DC-) - PE |
| Direction of action | (DC+/DC-) - PE |
| Nominal voltage U_N | 100 V DC ... 120 V DC |
| Maximum continuous voltage U_C | 150 V DC |
| Rated load current I_L | 40 A (Biconnect M4 fork-type cable lug 6 mm ²) 63 A (TWIN ferrule 2 x 10 mm ²) |
| Residual current I_{PE} | ≤ 10 μA DC |
| Nominal discharge current I_n (8/20) μs | 20 kA |
| Maximum discharge current I_{max} (8/20) μs | 40 kA |
| Impulse discharge current (10/350) μs, charge | 0.5 As |
| Impulse discharge current (10/350) μs, specific energy | 0.25 kJ/Ω |
| Impulse discharge current (10/350) μs, peak value I_{imp} | 1 kA |
| Total discharge current I_{total} (8/20) μs | 40 kA |
| Short-circuit current rating I_{SCCR} | 0.2 kA (without backup fuse) 6 kA (for 20 A gG/B backup fuse) |
| Voltage protection level U_p (DC+) - (DC-) | ≤ 1.8 kV |

VAL-SEC-T2-2+0-120DC-FM - Type 2 surge arrester



2907874

<https://www.phoenixcontact.com/us/products/2907874>

| | |
|---|-------------------------------------|
| Voltage protection level U_p (DC+/DC-) - PE | ≤ 0.85 kV |
| TOV behavior at U_T | 174 V DC (5 s / withstand mode) |
| Response time t_A | ≤ 25 ns |
| Max. backup fuse with V-type through wiring | 20 A (gG / B at $I_{SCCR} > 200$ A) |
| Max. backup fuse with branch wiring | 20 A (gG / B at $I_{SCCR} > 200$ A) |

Additional technical data

| | |
|----------------------------------|---|
| Maximum continuous voltage U_C | 135 V AC (for operation in safety lighting systems) |
|----------------------------------|---|

Environmental and real-life conditions

Ambient conditions

| | |
|---|---|
| Degree of protection | IP20 |
| Ambient temperature (operation) | -40 °C ... 80 °C |
| Ambient temperature (storage/transport) | -40 °C ... 80 °C |
| Altitude | ≤ 6000 m (amsl) |
| Permissible humidity (operation) | 5 % ... 95 % |
| Shock (operation) | 30g (Half-sine / 11 ms / 3x $\pm X$, $\pm Y$, $\pm Z$) |
| Vibration (operation) | 5g (10 ... 500 Hz / 2.5 h / X, Y, Z) |

Approvals

UL specifications

| | |
|---|---|
| Short-circuit current rating (SCCR) | 50 kA |
| Voltage protection rating VPR (DC+) - (DC-) | 1500 V |
| Voltage protection rating VPR (DC+) - G | 700 V |
| Voltage protection rating VPR (DC-) - G | 700 V |
| Nominal discharge current I_n | 20 kA |
| Mode of protection | (DC+) - (DC-) (DC+) - G (DC-) - G |
| Nominal voltage | 120 V DC |
| Power distribution system | DC |
| SPD Type | 1 |

UL indicator/remote signaling

| | |
|----------------------|----------|
| Operating voltage | 125 V AC |
| AC operating current | 1 A AC |

UL connection data

| | |
|-----------------------------|-------------------------|
| Tightening torque | 30 lb _F -in. |
| Conductor cross section AWG | 10 ... 2 |

Standards and regulations

| | |
|--------------------------|--------------|
| Standards/specifications | IEC 61643-11 |
| Note | 2011 |

VAL-SEC-T2-2+0-120DC-FM - Type 2 surge arrester



2907874

<https://www.phoenixcontact.com/us/products/2907874>

EN 61643-11

| | |
|--------------------------|-------------|
| Standards/specifications | EN 61643-11 |
| Note | 2012 |

Mounting

| | |
|---------------|-----------------|
| Mounting type | DIN rail: 35 mm |
|---------------|-----------------|

VAL-SEC-T2-2+0-120DC-FM - Type 2 surge arrester



2907874

<https://www.phoenixcontact.com/us/products/2907874>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27130805 |
| ECLASS-13.0 | 27171302 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC000941 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121600 |
|-------------|----------|

VAL-SEC-T2-2+0-120DC-FM - Type 2 surge arrester



2907874

<https://www.phoenixcontact.com/us/products/2907874>

Environmental product compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values |
|------------|---|

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com