

# RB UT 35-10 - Reducing bridge

3032168

<https://www.phoenixcontact.com/us/products/3032168>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Reducing bridge, pitch: 13.2 mm, number of positions: 2, color: red



## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 3032168       |
| Packing unit                         | 10 pc         |
| Minimum order quantity               | 10 pc         |
| Sales key                            | BE29          |
| Product key                          | BE2Z2X        |
| GTIN                                 | 4055626130934 |
| Weight per piece (including packing) | 10.25 g       |
| Weight per piece (excluding packing) | 10.25 g       |
| Customs tariff number                | 85366990      |
| Country of origin                    | PL            |

# RB UT 35-10 - Reducing bridge



3032168

<https://www.phoenixcontact.com/us/products/3032168>

## Technical data

### Product properties

|                     |                 |
|---------------------|-----------------|
| Product type        | Reducing bridge |
| Number of positions | 2               |
| Pitch               | 13.2 mm         |

### Electrical properties

|                      |   |
|----------------------|---|
| Maximum load current | 57 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.) |
|----------------------|---|

### Connection data

|                      |   |
|----------------------|---|
| Maximum load current | 57 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.) |
|----------------------|---|

### Dimensions

|       |         |
|-------|---------|
| Pitch | 13.2 mm |
|-------|---------|

### Material specifications

|  |        |
|--|--------|
| Color                                  | red    |
| Material                               | Copper |
| Flammability rating according to UL 94 | V0     |
| Insulating material                    | PA     |

### Environmental and real-life conditions

#### Ambient conditions

|                                 |        |
|---------------------------------|--------|
| Ambient temperature (operation) | 125 °C |
|---------------------------------|--------|

### Mounting

|               |                  |
|---------------|------------------|
| Mounting type | Plug-in mounting |
|---------------|------------------|

# RB UT 35-10 - Reducing bridge



3032168

<https://www.phoenixcontact.com/us/products/3032168>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141140 |
| ECLASS-12.0 | 27141140 |
| ECLASS-13.0 | 27250303 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000489 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# RB UT 35-10 - Reducing bridge



3032168

<https://www.phoenixcontact.com/us/products/3032168>

## Environmental product compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e<br>No hazardous substances above threshold values |
|------------|---|

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)