

DF-PTMC-U - Flange cover



3270401

<https://www.phoenixcontact.com/us/products/3270401>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Flange cover, for direct mounting below, depth: 12.8 mm, width: 22 mm, height: 29.1 mm, color: gray

Your advantages

- Easy marking options
- Enables wall mounting of PTMC
- Accessories for snapping on to PTMC

Commercial data

Item number	3270401
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BE69
Product key	BE6ZWX
Catalog page	Page 57 (C-1-2019)
GTIN	4055626061061
Weight per piece (including packing)	1.84 g
Weight per piece (excluding packing)	1.81 g
Customs tariff number	85389099
Country of origin	PL

DF-PTMC-U - Flange cover



3270401

<https://www.phoenixcontact.com/us/products/3270401>

Technical data

Product properties

Product type	Mounting material
--------------	-------------------

Dimensions

Width	22 mm
Height	29.1 mm
Depth	12.8 mm

Material specifications

Color	gray
Material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	27,5 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

DF-PTMC-U - Flange cover

3270401

<https://www.phoenixcontact.com/us/products/3270401>



Classifications

ECLASS

ECLASS-11.0	27141133
ECLASS-12.0	27141133
ECLASS-13.0	27250301

ETIM

ETIM 9.0	EC000886
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

DF-PTMC-U - Flange cover

3270401

<https://www.phoenixcontact.com/us/products/3270401>



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com