

# UCT-WMT (12X4) CUS - Conductor marker



0801522

<https://www.phoenixcontact.com/us/products/0801522>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Conductor marker, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: insert, cable diameter range: 0.6 ... 10 mm, lettering field size: 12 x 4 mm, Number of individual labels: 50



## Commercial data

Item number	0801522
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	BG8128
Catalog page	Page 183 (C-5-2013)
GTIN	4046356682688
Weight per piece (including packing)	14.9 g
Weight per piece (excluding packing)	10.9 g
Country of origin	PL

# UCT-WMT (12X4) CUS - Conductor marker



0801522

<https://www.phoenixcontact.com/us/products/0801522>

## Technical data

### Product properties

Product type	Labeled conductor marker
--------------	--------------------------

### Marking

Number of individual labels	50
Number of individual labels per row	10
Identification technology	Thermal transfer for sheets and cards

### Mounting

Mounting type	insert
---------------	--------

### Material specifications

RoHS compliant	yes
Color	white
Material	PC V0
Flammability rating according to UL 94	V0
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Components	free from silicone and halogen

### Environmental and real-life conditions

#### Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

#### UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 120 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %

### Dimensions

Width	12 mm
Length	4 mm

### Standards and regulations

# UCT-WMT (12X4) CUS - Conductor marker



0801522

<https://www.phoenixcontact.com/us/products/0801522>

Wipe resistance

DIN EN 61010-1 (VDE 0411-1)

# UCT-WMT (12X4) CUS - Conductor marker



0801522

<https://www.phoenixcontact.com/us/products/0801522>

## Classifications

### ECLASS

ECLASS-11.0	27281106
ECLASS-12.0	27281106
ECLASS-13.0	27281106

### ETIM

ETIM 9.0	EC001530
----------	----------

### UNSPSC

UNSPSC 21.0	39131700
-------------	----------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)