

NS 35/ 7,5 ZN PERF (18X5,2) 2M - DIN rail perforated



0804278

<https://www.phoenixcontact.com/us/products/0804278>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



DIN rail perforated, Hole size: 5.2 mm x 18 mm, acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

Commercial data

Item number	0804278
Packing unit	25 m
Minimum order quantity	25 m
Sales key	BE72
Product key	BE7242
Catalog page	Page 527 (C-3-2019)
GTIN	4055626277943
Weight per piece (including packing)	1,272 g
Weight per piece (excluding packing)	1,272 g
Customs tariff number	72166190
Country of origin	DE

NS 35/ 7,5 ZN PERF (18X5,2) 2M - DIN rail perforated



0804278

<https://www.phoenixcontact.com/us/products/0804278>

Technical data

Product properties

Product type	DIN rail
--------------	----------

Dimensions

Width	35 mm
Hole width	18 mm
Height	2000 mm
Hole height	5.2 mm
Depth	7.5 mm
Length	2000 mm
Drill hole spacing	25 mm

Material specifications

Color	silver
Material	Steel
Coating	galvanized

Standards and regulations

Tests	acc. to EN 60715
-------	------------------

NS 35/ 7,5 ZN PERF (18X5,2) 2M - DIN rail perforated



0804278

<https://www.phoenixcontact.com/us/products/0804278>

Classifications

ECLASS

ECLASS-11.0	27400602
ECLASS-13.0	27400602
ECLASS-12.0	27400602

ETIM

ETIM 9.0	EC001285
----------	----------

UNSPSC

UNSPSC 21.0	39121700
-------------	----------

NS 35/ 7,5 ZN PERF (18X5,2) 2M - DIN rail perforated



0804278

<https://www.phoenixcontact.com/us/products/0804278>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com