

0831076

https://www.phoenixcontact.com/us/products/0831076



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Identification label for flow-through substances with centered hole for addition fixing with a pop rivet, for assembling the CARRIER-PMP (110x38), CARRIER/L-PMP (110x38) and CARRIER-PMP-ENCLOSED (110x38) according to DIN 2403

Commercial data

| Item number | 0831076 |
|--------------------------------------|---------------------|
| Packing unit | 100 pc |
| Minimum order quantity | 100 pc |
| Product key | BG261Z |
| Catalog page | Page 365 (C-3-2019) |
| GTIN | 4046356941099 |
| Weight per piece (including packing) | 0.594 g |
| Weight per piece (excluding packing) | 0.505 g |
| Country of origin | DE |

PMST (10X38) - Insert label

0831076

https://www.phoenixcontact.com/us/products/0831076



Technical data

Product properties

| Product type | Labeled systems marker |
|---------------------------------------|---|
| Area of application | Identification of flow substances according to DIN 2403 |
| | Identification of flow substances according to DIN 2403 |
| | |
| arking Number of individual labels | 1 |

Dimensions


| Width | 10 mm |
|--------|-------|
| Length | 38 mm |

Material specifications

| Color | white |
|--|--------------------------------|
| Material | PVC |
| Flammability rating according to UL 94 | V0 |
| Components | Free from silicone and cadmium |

Environmental and real-life conditions

| UV resistance | | |
|---|--|--|
| Specification | ISO 4892-2:2013-03 (following) | |
| Result | Test passed | |
| Test duration | 96 h | |
| Ambient conditions | | |
| Ambient temperature (operation) | -30 °C 80 °C | |
| Recommended ambient temperature (storage/transport) | 10 °C 30 °C | |
| Recommended humidity (storage/transport) | 40 % 70 % (Storage in a dry and dark place in the original packaging is recommended) | |
| Shelf life | 12 months | |
| Standards and regulations | | |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) | |
| lounting | | |
| Mounting type | snapped | |
| | | |



0831076

https://www.phoenixcontact.com/us/products/0831076



Classifications

ECLASS

| ECLASS-12.0 27281104 | |
|----------------------|--|
| | |
| ECLASS-13.0 27281104 | |

ETIM

| | ETIM 9.0 | EC001288 | |
|----|-------------|----------|--|
| U١ | UNSPSC | | |
| | UNSPSC 21.0 | 39131500 | |

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com