

# C S6 A 600X600X300 - Empty enclosure



0899128

<https://www.phoenixcontact.com/us/products/0899128>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Empty enclosure, material: Stainless steel, 316L/1.4404, surface resistance: brushed, silver, 600 mm x 600 mm x 300 mm, type of locking: Door with replaceable hinge, scope of supply - ATD: Door hinge with quarter turn locking, Mounting panel, Double-bit key, Fixing angle with mounting screws, M12 grounding bolts, affixed externally, Installation notes, Door hinge with quarter turn locking

## Commercial data

Item number	0899128
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	NULL
Product key	BH9112
Catalog page	Page 635 (C-3-2019)
GTIN	4046356928908
Weight per piece (including packing)	27.16 kg
Weight per piece (excluding packing)	27.16 kg
Customs tariff number	94032080
Country of origin	DE

# C S6 A 600X600X300 - Empty enclosure



0899128

<https://www.phoenixcontact.com/us/products/0899128>

## Technical data

### Product properties

Product type	Terminal box
Scope of delivery	Door hinge with quarter turn locking
	Mounting panel
	Double-bit key
	Fixing angle with mounting screws
	M12 grounding bolts, affixed externally
Installation notes	
Type	32


### Insulation characteristics

Protection class	I
------------------	---

### Electrical properties

Maximum power dissipation	39 W (T6 up to 40 °C)
	24.3 W (T6 up to 55 °C)
	14.6 W (T6 up to 65 °C)
	53.6 W (T5 up to 40 °C)
	39 W (T5 up to 55 °C)
	29.3 W (T5 up to 65 °C)
	63.4 W (T4 up to 40 °C)
	30.5 W (T4 up to 55 °C)
39 W (T4 up to 65 °C)	

### Dimensions

Dimensional drawing	
Width	600 mm
Height	600 mm
Depth	300 mm
Clearance width, maximum DIN rail length	1632 mm
Max. material thickness	2 mm

### Material specifications

Color	silver
Material	Stainless steel, 316L/1.4404

# C S6 A 600X600X300 - Empty enclosure



0899128

<https://www.phoenixcontact.com/us/products/0899128>

Seal material	Silicon
Surface characteristics	brushed
Note	240 grain

## Mechanical properties

### General

Type of locking (GRP)	Door with replaceable hinge Quarter turn locking with two-way key bit
-----------------------	---

## Environmental and real-life conditions

### Ambient conditions

Ambient temperature (operation)	-55 °C ... 135 °C
---------------------------------	-------------------

## Mounting

Assembly instructions	External fixing clips
-----------------------	-----------------------

# C S6 A 600X600X300 - Empty enclosure



0899128

<https://www.phoenixcontact.com/us/products/0899128>

## Classifications

### ECLASS

ECLASS-11.0	27180101
ECLASS-12.0	27180101
ECLASS-13.0	27180101

### ETIM

ETIM 9.0	EC000261
----------	----------

### UNSPSC

UNSPSC 21.0	31261500
-------------	----------

# C S6 A 600X600X300 - Empty enclosure



0899128

<https://www.phoenixcontact.com/us/products/0899128>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)