0899136

https://www.phoenixcontact.com/us/products/0899136

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Empty enclosure, material: Stainless steel, 316L/1.4404, surface resistance: brushed, silver, 740 mm x 980 mm x 300 mm, type of locking: Door with replaceable hinge, scope of supply - ATD: Door hinge with quarter turn locking, Mounting panel, Double-bit key, Fixing angle with mounting screws, M12 grounding bolts, affixed externally, Installation notes, Door hinge with quarter turn locking

### Commercial data

Item number	0899136
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	NULL
Product key	BH9112
Catalog page	Page 635 (C-3-2019)
GTIN	4046356928984
Weight per piece (including packing)	47.26 kg
Weight per piece (excluding packing)	47.26 kg
Customs tariff number	94032080
Country of origin	DE

PHŒN

0899136

https://www.phoenixcontact.com/us/products/0899136

## Technical data

### Product properties

Product type	Terminal box
Scope of delivery	Door hinge with quarter turn locking
	Mounting panel
	Double-bit key
	Fixing angle with mounting screws
	M12 grounding bolts, affixed externally
	Installation notes
Туре	34
sulation characteristics	
Protection class	1
ectrical properties	
Maximum power dissipation	61 W (T6 up to 40 °C)
	38.1 W (T6 up to 55 °C)
	22.8 W (T6 up to 65 °C)
	83.9 W (T5 up to 40 °C)

45.8 W (T5 up to 65 °C) 99.1 W (T4 up to 40 °C) 47.7 W (T4 up to 55 °C) 61 W (T4 up to 65 °C)

#### Dimensions

Dimensional drawing	
Width	740 mm
Height	980 mm
Depth	300 mm
Clearance width, maximum DIN rail length	2736 mm
Max. material thickness	2 mm

#### Material specifications

Color	silver
Material	Stainless steel, 316L/1.4404

PHŒNIX ICONTACT

#### 0899136

https://www.phoenixcontact.com/us/products/0899136

Silicon		
brushed		
240 grain		
Mechanical properties		
Door with replaceable hinge Quarter turn locking with two-way key bit		
Environmental and real-life conditions Ambient conditions		
-55 °C 135 °C		
Mounting		
External fixing clips		

**DPHŒNIX** CONTACT 0899136

https://www.phoenixcontact.com/us/products/0899136



### Classifications

#### ECLASS

ECLASS-11.0	27180101
ECLASS-12.0	27180101
ECLASS-13.0	27180101

#### ETIM

	ETIM 9.0	EC000261
UNSPSC		
	UNSPSC 21.0	31261500

0899136

https://www.phoenixcontact.com/us/products/0899136

# 

### Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com