

https://www.phoenixcontact.com/us/products/1002635

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Modular power distribution board with CrossLink<sup>®</sup> interface, 125 A, 3-pos., touch-proof and protection against polarity reversal, width: 405 mm



### Your advantages

- · Protection against polarity reversal phase rotation not possible
- Quick, complete out-of-the-box system
- · Compact design compared to conventional power distribution

### Commercial data

Item number	1002635
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C470
Product key	CK7811
Catalog page	Page 52 (C-5-2019)
GTIN	4055626468204
Weight per piece (including packing)	1,410.3 g
Weight per piece (excluding packing)	1,367.3 g
Customs tariff number	85369095
Country of origin	DE

PHŒN

1002635

https://www.phoenixcontact.com/us/products/1002635

## Technical data

#### Product properties

	Product type	Assembly adapter
Produ	Product family	CrossPowerSystem
Electrical properties		
	Rated voltage	600 V DC (IEC)
		690 V AC (IEC)
		600 V AC/DC (UL)
	Rated peak withstand current	25 kA
	Rated current	125 A (IEC)
		100 A (UL)
	Rated insulation voltage	800 V AC
	Rated surge voltage	6 kV

#### Dimensions

Width	405 mm
Height	160 mm
Depth	45.1 mm

#### Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP20

#### Approvals

JL data	
SCCR	10 kA (unprotected)
	100 kA (protected)
	100 kA (CB 125 A/480 V AC)
	65 kA (CB 125 A/600 V AC)
	100 A (Class J 175 A)

#### Standards and regulations

Standards/regulations	IEC 61439-2
	GB/T 7251.1

PHŒN

X



https://www.phoenixcontact.com/us/products/1002635



## Classifications

#### ECLASS

ECLASS-11.0	27371392
ECLASS-13.0	27371392
ECLASS-12.0	27371392

#### ETIM

	ETIM 9.0	EC002498
UNSPSC		
	UNSPSC 21.0	39121100

1002635

https://www.phoenixcontact.com/us/products/1002635

### **PHŒNIX** CONTACT

### Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com