

RJ45 connector - CUC-IND-C1ZNI-S/R4QV6:30 - 1406353

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



RJ45 connector, degree of protection: IP20, number of positions: 6, 100 Mbps, CAT5 (IEC 11801:2002), material: Zinc die-cast, connection method: IDC fast connection, connection cross section: AWG 26- 24, cable outlet: straight, High degree of resistance to vibration; 360° shielding; one-piece design; special tool-free assembly, VARAN

Your advantages

- ✓ assembly without special tools
- ✓ One-Piece Design
- ✓ 360° shielding
- ✓ High shock and vibration resistance
- ✓ Value pack with 30 pcs.



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| Minimum order quantity | 30 pc |
| GTIN |  4 046356 760997 |
| GTIN | 4046356760997 |
| Weight per Piece (excluding packing) | 16.000 g |
| Custom tariff number | 85366990 |
| Country of origin | Poland |

Technical data

Mechanical characteristics

| | |
|-------------------------------------|---------------------|
| Connection method | IDC fast connection |
| Minimum external conductor diameter | 5 mm |
| Maximum external conductor diameter | 9 mm |
| AWG solid min. | 26 |

RJ45 connector - CUC-IND-C1ZNI-S/R4QV6:30 - 1406353

Technical data

Mechanical characteristics

| | |
|--|--|
| AWG solid max. | 24 |
| AWG multi-stranded min. | 23 |
| AWG multi-stranded max. | 22 |
| Cable outlet | straight |
| No. of cable outlets | 1 |
| Conductor cross section | 4x 0.25 mm ² ... 0.34 mm ² (Data (solid and stranded)) |
| | 2x 0.32 mm ² (Power (solid and stranded)) |
| Weight | 15.99 g |
| Flammability rating according to UL 94 | V0 |

Ambient conditions

| | |
|---------------------------------|------------------|
| Ambient temperature (operation) | -40 °C ... 70 °C |
|---------------------------------|------------------|

Material data

| | |
|----------------------------|------------------|
| Contact surface material | Gold over nickel |
| Contact material | Copper alloy |
| Contact carrier material | PC |
| Housing material | Zinc die-cast |
| Width | 13.65 mm |
| Height | 53 mm |
| Length | 14.4 mm |
| Housing material | GD-Zn |
| Housing surface material 1 | Nickel-plated |

Electrical characteristics

| | |
|---|---|
| Number of positions | 6 |
| Nominal voltage U _N | 48 V |
| Transmission speed | 100 Mbps |
| Transmission characteristics (category) | CAT5 (IEC 11801:2002) |
| GRP transmission properties | CAT5 (IEC 11801:2002) CAT5 (IEC 11801:2002) |
| Transmission speed | 100 Mbps |
| Frequency range | to 100 MHz |
| Rated current | 1.75 A |
| Rated voltage (III/3) | 72 V (DC) |

Standards and Regulations

| | |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|

RJ45 connector - CUC-IND-C1ZNI-S/R4QV6:30 - 1406353


Technical data

Environmental Product Compliance

| | |
|--|--|
| | No hazardous substances above threshold values |
|--|--|

Drawings

Dimensional drawing



Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27440101 |
| eCl@ss 11.0 | 27440101 |
| eCl@ss 4.0 | 27260700 |
| eCl@ss 4.1 | 27260700 |
| eCl@ss 5.0 | 27260700 |
| eCl@ss 5.1 | 27260700 |
| eCl@ss 6.0 | 27260700 |
| eCl@ss 7.0 | 27440101 |
| eCl@ss 9.0 | 27440101 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002643 |
| ETIM 6.0 | EC002636 |
| ETIM 7.0 | EC002636 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11 | 39121409 |
| UNSPSC 12.01 | 39121409 |
| UNSPSC 13.2 | 39121409 |
| UNSPSC 18.0 | 39121409 |

RJ45 connector - CUC-IND-C1ZNI-S/R4QV6:30 - 1406353

Classifications

UNSPSC

| | |
|-------------|----------|
| UNSPSC 19.0 | 39121409 |
| UNSPSC 20.0 | 39121409 |
| UNSPSC 21.0 | 39121409 |

Approvals


Approvals

Approvals

EAC

Ex Approvals

Approval details

| | | |
|-----|---|---------|
| EAC |  | B.01687 |
|-----|---|---------|
