

QPD P 2PE1,5 4-9 BK - Connector



1414705

<https://www.phoenixcontact.com/us/products/1414705>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Connector, product family: QPD, connection method: IDC connection, number of positions: 2+PE, 0.5 mm² ... 1.5 mm², 690 V, 17.5 A, PA, black, with QUICKON nut, external cable diameter: 5 mm ... 9.5 mm

Your advantages

- Innovative and time saving - QUICKON fast connection for time saving of up to 80 % for on-site connection
- Robust throughout: housing with IP68/IP69K and IK07 protection for a wide range of applications
- Safer connection with mechanical coding to protect against mismatching, and touch-proof protection in accordance with DIN EN 0105
- Easy maintenance – the connectors enable fast device replacement and preassembled cables simplify startup

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 1414705 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | BF50 |
| Product key | BF6BAA |
| Catalog page | Page 479 (C-2-2019) |
| GTIN | 4055626031675 |
| Weight per piece (including packing) | 39.5 g |
| Weight per piece (excluding packing) | 39.5 g |
| Customs tariff number | 85366990 |
| Country of origin | PL |

QPD P 2PE1,5 4-9 BK - Connector



1414705

<https://www.phoenixcontact.com/us/products/1414705>

Technical data

Product properties

| | |
|------------------------------------|------------------------|
| Type | QPD 3x1,5 |
| Product type | Installation connector |
| Product family | QPD |
| Number of positions | 3 |
| Connection profile | 2+PE |
| Position marking | 1, 2, PE |
| Number of connections | 3 |
| Number of connections per position | 1 |
| Coding | Coding profile |

Insulation characteristics

| | |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution | 3 |

Electrical properties

| | |
|-----------------------------|----------------------|
| Rated surge voltage (II/2) | 8 kV |
| Rated surge voltage (III/2) | 8 kV |
| Rated surge voltage (III/3) | 6 kV |
| Rated current | 17.5 A |
| Contact resistance | < 3 mΩ |
| rated voltage (II/2) | 1000 V |
| rated voltage (III/2) | 1000 V |
| Rated voltage (III/3) | 690 V |
| Nominal voltage U_N | 690 V AC 690 V DC |
| Nominal current I_N | 17.5 A |

Connection data

Connection technology

| | |
|---|----------------|
| Connection method On the field side | IDC connection |
| Frequency of connections between conductors of the same cross section | max. 10 |

Conductor connection


| | |
|----------------------------------|---|
| Conductor cross section flexibel | 0.5 mm ² ... 1.5 mm ² |
| Conductor cross section solid | 0.5 mm ² ... 1.5 mm ² |
| Connection cross section AWG | 20 ... 16 |
| Tightening torque Union nut | 8 Nm |
| Tightening torque Locking nut | 5 Nm |

Dimensions

QPD P 2PE1,5 4-9 BK - Connector

1414705

<https://www.phoenixcontact.com/us/products/1414705>

| | |
|---------------------|--|
| Dimensional drawing |  |
| Width | 25 mm |
| Height | 25 mm |
| Length | 70.8 mm |
| Diameter | 25 mm |

Material specifications

| | |
|--|------------------------|
| Color | black (RAL 9005) |
| Material Housing | PA |
| Material Contact | Cu |
| Material Contact surface | Silver-plated |
| Flammability rating according to UL 94 | V0 |
| Material wire insulation | PVC /PE / rubber / TPE |

Cable/line

| | |
|---|------------------------------------|
| Structure of individual litz in acc. with VDE 0295 / smallest wire diameter | VDE 0295 class 1 to 6/min. 0.15 mm |
| External cable diameter () | 5 mm ... 9.5 mm |
| Wire diameter including insulation | 1.6 mm ... 3 mm |
| Position marking | 1, 2, PE |
| Material wire insulation | PVC/PE/TPE/rubber |

Mechanical properties

Mechanical data

| | |
|-----------------------------|---------|
| Insertion/withdrawal cycles | max. 50 |
|-----------------------------|---------|

Environmental and real-life conditions

Ambient conditions

| | |
|---|------------------------------------|
| Degree of protection | IP66 IP68 (2 m / 24 h) IP69K |
| Ambient temperature (operation) | -40 °C ... 100 °C |
| Temperature when conductor connected | -5 °C ... 50 °C |
| Ambient temperature (storage/transport) | -40 °C ... 100 °C |

QPD P 2PE1,5 4-9 BK - Connector



1414705

<https://www.phoenixcontact.com/us/products/1414705>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27440605 |
| ECLASS-12.0 | 27440605 |
| ECLASS-13.0 | 27440605 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC002560 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

QPD P 2PE1,5 4-9 BK - Connector



1414705

<https://www.phoenixcontact.com/us/products/1414705>

Environmental product compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values |
|------------|---|

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com