

# SACC-BP-F-FIX/NUT-BK-THR - Fixing sleeve



1419697

<https://www.phoenixcontact.com/us/products/1419697>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Fixing sleeve for M12 housing screw connection with tolerance-compensating function, for THR solderable M12 socket contact inserts.

## Commercial data

Item number	1419697
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	AB23
Product key	ABQADG
GTIN	4055626189468
Weight per piece (including packing)	2.02 g
Weight per piece (excluding packing)	1.04 g
Customs tariff number	39269097
Country of origin	DE

# SACC-BP-F-FIX/NUT-BK-THR - Fixing sleeve



1419697

<https://www.phoenixcontact.com/us/products/1419697>

## Technical data

### Notes

General	The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
---------	--

### Product properties

Product type	Panel mounting base
Thread type	M12

### Connection data

Connection method	THR solder connection
-------------------	-----------------------

### Material specifications

Color	black (Fixing sleeve)
Material	PA 6.6
Flammability rating according to UL 94	V0
Seal material	FKM

### Connector

#### Connection 1

Head design	Socket
Head thread type	M12

### Mechanical properties

#### Mechanical data

Insertion/withdrawal cycles	> 100
-----------------------------	-------

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection (when plugged in)	IP67 (correctly plugged in and locked)
Degree of protection	IP67 (correctly plugged in and locked) IP67, when in locked state
Ambient temperature (operation)	-25 °C ... 85 °C (Plug / socket) -40 °C ... 85 °C (without mechanical actuation)

### Standards and regulations

#### M12

Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101

# SACC-BP-F-FIX/NUT-BK-THR - Fixing sleeve



1419697

<https://www.phoenixcontact.com/us/products/1419697>

Note	In line with
------	--------------

## Mounting

Mounting type	Rear mounting 2-section, lockable
Assembly instructions	2-section, lockable

# SACC-BP-F-FIX/NUT-BK-THR - Fixing sleeve



1419697

<https://www.phoenixcontact.com/us/products/1419697>

## Classifications

### ECLASS

ECLASS-11.0	27440224
ECLASS-12.0	27440224
ECLASS-13.0	27440224

### ETIM

ETIM 9.0	EC003556
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# SACC-BP-F-FIX/NUT-BK-THR - Fixing sleeve



1419697

<https://www.phoenixcontact.com/us/products/1419697>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)