

1424396

https://www.phoenixcontact.com/us/products/1424396

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Box mounting bases D25, with single locking latch, material: Die-cast aluminum, salt water resistant, protective cover material: PC, cable outlets: 2, lateral, 2x M20, height: 57 mm, cable gland: none, protective cover: yes, Standard

Commercial data

Item number	1424396
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF56
Product key	BF7APE
Catalog page	Page 531 (C-2-2019)
GTIN	4055626371368
Weight per piece (including packing)	224.4 g
Weight per piece (excluding packing)	185 g
Customs tariff number	85389099
Country of origin	CN



1424396

https://www.phoenixcontact.com/us/products/1424396

Technical data

Product properties

Туре	D25
Product type	Housing with locking latch
Product family	HC-STA-D
Application	Standard
No. of cable outlets	2
Type of the screw connection	2x M20
Housing type	Box mounting bases
Protective cover	yes
Cable outlet	lateral
Pg screw connection	none

Dimensions

Dimensional drawing	96.5
Width	51 mm
Height	57 mm
Length	80 mm
Hole diameter	4.5 mm

Material specifications

Flammability rating according to UL 94	V0 (Interlock)
	V0 (Protective cover)
Housing surface material	uncoated
Material, protective cover	PC
Locking latch material	PA
Impact strength	IK08
Housing material	Die-cast aluminum, salt water resistant

Mechanical properties

Mechanical data

Type of the screw connection	2x M20
Locking type	Latch

Mounting

Assembly instructions	One opening is sealed with a plastic filler plug and can be
	opened using a screwdriver.



1424396

https://www.phoenixcontact.com/us/products/1424396

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66 (with locked protective cover)
	IP67 (when plugged in)
Impact strength	IK08
Ambient temperature (operation)	-40 °C 125 °C



1424396

https://www.phoenixcontact.com/us/products/1424396

Classifications

ECLASS

	ECLASS-11.0	27440202
	ECLASS-12.0	27440202
	ECLASS-13.0	27440202
ETIM		
	ETIM 9.0	EC000437
UNSPSC		
	UNSPSC 21.0	31261500



1424396

https://www.phoenixcontact.com/us/products/1424396

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com