

## Fiber optic contact insert - FOC-HC-2SC-MM 2,8 - 1425940

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Fiber optic contact insert, degree of protection: IP20, cable outlet: straight, Ethernet

### Product Description

2x SC Simplex connectors for 50/125 µm (multimode) for conventional adhesive assembly, including crimping sleeve, only for installation in HEAVYCON insert 1419889



### Key Commercial Data

Packing unit	1
GTIN	 4 055626 432021
GTIN	4055626432021
Custom tariff number	85367000

### Technical data

#### Mechanical characteristics

Minimum external conductor diameter	2.7 mm
Maximum external conductor diameter	2.9 mm
Insertion/withdrawal cycles	≥ 100
Cable outlet	straight
No. of cable outlets	1
Weight	6.2 g
Flammability rating according to UL 94	V0

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (assembly)	-5 °C ... 50 °C

## Fiber optic contact insert - FOC-HC-2SC-MM 2,8 - 1425940

### Technical data

#### Ambient conditions

Ambient temperature (storage/transport)	-40 °C ... 85 °C
Degree of protection	IP20

#### Material data

Width	5.96 mm
Height	6.76 mm

#### Standards and Regulations

Resistance to UV radiation	yes
Flammability rating according to UL 94	V0

#### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

### Classifications

#### eCl@ss

eCl@ss 10.0.1	27440205
eCl@ss 11.0	27440223
eCl@ss 5.1	27261200
eCl@ss 6.0	27261200
eCl@ss 7.0	27440205
eCl@ss 9.0	27440205

#### ETIM

ETIM 6.0	EC000438
ETIM 7.0	EC000438

#### UNSPSC

UNSPSC 13.2	43223310
UNSPSC 18.0	39121522
UNSPSC 19.0	39121522
UNSPSC 20.0	39121522
UNSPSC 21.0	39121522