

EV-CC-AC1-M3-CBC-SER-PCB-XC-25 - AC charging controller



1627743

<https://www.phoenixcontact.com/us/products/1627743>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



The EV-CC-AC1-M3-CBC-SER-PCB charging controller as PCB is used for charging electric vehicles at 3-phase AC networks according to IEC 61851-1, Mode 3. All charging functions, comprehensive configuration settings as well as a locking controller are already integrated.

Commercial data

| | |
|--------------------------------------|--------------------|
| Item number | 1627743 |
| Packing unit | 25 pc |
| Minimum order quantity | 25 pc |
| Product key | XWBBAB |
| Catalog page | Page 64 (C-7-2019) |
| GTIN | 4055626364483 |
| Weight per piece (including packing) | 209 g |
| Weight per piece (excluding packing) | 209 g |
| Country of origin | DE |

EV-CC-AC1-M3-CBC-SER-PCB-XC-25 - AC charging controller



1627743

<https://www.phoenixcontact.com/us/products/1627743>

Technical data

Product properties

| | |
|----------------|--|
| Product type | AC charging controller |
| Product family | CHARX control basic |
| Application | AC charging controller for private and commercial applications (EU/CN) |
| Operating mode | Stand-Alone Client |
| Charging mode | Mode 3, Case B + C |

System properties

Charging controllers

| | |
|---------------------------|---|
| Number of charging points | 1 |
|---------------------------|---|

Electrical properties

| | |
|---|---|
| Type of charging current | AC |
| Current consumption | < 1 W |
| Locking release in the event of mains failure | Integrated release function of the locking actuator for disconnection of Infrastructure Plug and Infrastructure Socket Outlet |

Supply

| | |
|---------------------------|---|
| Supply voltage | 230 V |
| Supply voltage range | 100 V AC ... 240 V AC (nominal voltage range) |
| Max. current consumption | 40 mA |
| Nominal power consumption | < 1 W (No-load) |
| Frequency range | 50 Hz ... 60 Hz |

Input data

Digital

| | |
|-----------------------------|-------------------|
| Number of digital inputs | 5 |
| Frequency range | 50 Hz ... 60 Hz |
| Nominal power consumption | < 0.5 W (No-load) |
| Nominal current I_N | ≤ 1 mA |
| Nominal input voltage U_N | 12 V |
| Input voltage range U1 | 0 V ... 3 V (Off) |
| Input voltage range U2 | 9 V ... 15 V (On) |

Output data

Digital

| | |
|-------------|-------------------|
| Output name | 4 digital outputs |
|-------------|-------------------|

EV-CC-AC1-M3-CBC-SER-PCB-XC-25 - AC charging controller



1627743

<https://www.phoenixcontact.com/us/products/1627743>

| | |
|------------------------|---|
| Connection technology | Screw connection |
| Maximum output voltage | 30 V |
| Maximum output current | 0.5 A (Total current for all outputs; internally supplied) 0.6 A (Per output; externally supplied) |

Switching

| | |
|----------------------------|-------------------------------|
| Output name | Relay output C _{1,2} |
| Minimum switching capacity | 1500 VA |
| Maximum switching voltage | 250 V AC (External supply) |
| Max. switching current | 6 A |

Switching

| | |
|----------------------------|------------------------|
| Output name | Relay output LO+/- |
| Minimum switching capacity | 24 VA |
| Maximum switching voltage | 12 V (Internal supply) |
| Max. switching current | 2 A |

Connection data

Conductor connection

| | |
|----------------------------------|---|
| Connection method | Screw connection |
| Conductor cross section rigid | 0.2 mm ² ... 4 mm ² |
| Conductor cross section flexible | 0.2 mm ² ... 2.5 mm ² |
| Conductor cross section AWG | 24 ... 12 |

Interfaces

| | |
|-----------|--------|
| Interface | RS-485 |
|-----------|--------|

RS-485

| | |
|-----------------------------|-------------------------------------|
| Interface | RS-485 2-wire |
| Bus system | RS-485 |
| Connection method | Screw connection |
| Number of interfaces | 1 |
| Transmission speed | 9.6 kbps (Standard) |
| Transmission speed range | 9.6 kbps ... 19.2 kbps (adjustable) |
| Data flow control/protocols | Modbus/RTU (slave) |

Environmental and real-life conditions

Ambient conditions

| | |
|---|------------------|
| Degree of protection | IP00 |
| Ambient temperature (operation) | -35 °C ... 70 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |
| Permissible humidity (operation) | 30 % ... 95 % |

EV-CC-AC1-M3-CBC-SER-PCB-XC-25 - AC charging controller



1627743

<https://www.phoenixcontact.com/us/products/1627743>

Approvals

Conformity/Approvals

| | |
|-------------|--------------|
| Conformance | CE-compliant |
|-------------|--------------|

Standards and regulations

Standards

| | |
|-----------------------|-------------|
| Standards/regulations | IEC 61851-1 |
|-----------------------|-------------|

Mounting

| | |
|-------------------|--------------|
| Mounting type | PCB mounting |
| Mounting position | any |

EV-CC-AC1-M3-CBC-SER-PCB-XC-25 - AC charging controller



1627743

<https://www.phoenixcontact.com/us/products/1627743>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27144703 |
| ECLASS-12.0 | 27144703 |
| ECLASS-13.0 | 27144703 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC002889 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121800 |
|-------------|----------|

EV-CC-AC1-M3-CBC-SER-PCB-XC-25 - AC charging controller



1627743

<https://www.phoenixcontact.com/us/products/1627743>

Environmental product compliance

| | |
|------------|--|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com