

1628001

https://www.phoenixcontact.com/us/products/1628001

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



CHARX connect comfort, Mobile AC charging cable, with vehicle charging connector and infrastructure charging plug, For charging electric vehicles (EV) with alternating current (AC) via GB/T vehicle charging inlets, with protective cap, with locking option for padlock, GB/T, Type 2, IEC 62196-2, GB/T 20234.2-2015, housing: black, gray, PHOENIX CONTACT logo, cable: 5 m, black, straight

### Product description

Mobile AC charging cable with vehicle charging connector and infrastructure charging plug for charging electric vehicles (EV) with alternating current (AC) via GB/T vehicle charging inlets, compatible with type 2 infrastructure charging sockets at charging stations for e-mobility (EVSE)

#### Your advantages

- · Complete product range
- · Convenient handling due to the ergonomic, triple award-winning design
- Available with your logo on request for consistent branding of your charging station
- · Longitudinal water tightness reliably prevents water ingress
- Developed and produced in accordance with the IATF 16949 automotive standard and ISO 9001
- Tested in accordance with automotive standards LV124, LV214, and LV215-2
- · Tested in accordance with EV Ready 37 requirements

#### Commercial data

Item number	1628001
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	EM01
Product key	XWBAEH
Catalog page	Page 33 (C-7-2019)
GTIN	4055626370156
Weight per piece (including packing)	3,418 g
Weight per piece (excluding packing)	3,418 g
Customs tariff number	85444290
Country of origin	PL



1628001

https://www.phoenixcontact.com/us/products/1628001

#### Technical data

### Product properties

Product type	AC charging cable
Product family	CHARX connect comfort
Application	For charging electric vehicles (EV) with alternating current (AC) via GB/T vehicle charging inlets
	compatible with type 2 infrastructure charging sockets at charging stations for electromobility (EVSE)
Туре	Mobile AC charging cable
	with vehicle charging connector and infrastructure charging plug
Design	with protective cap
	with locking option for padlock
Affixed logo	PHOENIX CONTACT logo
Charging mode	Mode 3, Case B
Charging standard	GB/T
	Type 2

#### Electrical properties

Type of charging current	AC 3-phase
Charging power	26.6 kW
Charging current	32 A

#### Material specifications

Color (Housing)	black (9005)
Color (Handle area)	black (9005)
Color (Mating face)	black (9005)
Color (Protective cap)	black (9005)
Color (Cable)	black (9005)

#### Cable/line

Cable length	5 m
Wiring standards/regulations	prEN 50620/DIN EN 50620
Wiring certifications	VDE
Cable weight	max. 505.00 kg/km
Cable type	Class 5
Cable type	straight
Cable structure	5 x 6.0 mm² + 1 x 0.5 mm²
External cable diameter	17.00 mm ±0.4 mm
Outer sheath, material	TPE-U
Stripping length of the sheath	60 mm ±15 mm
Stripping length	60 mm ±15 mm
Cable resistance	$\leq$ 0.0033 $\Omega$ /m (based on a power core, at an ambient temperature of 20°C)



1628001

https://www.phoenixcontact.com/us/products/1628001

Bending radius	min. 127.5 mm (7.5x diameter)
Cable length	5 m
Stripping length	60 mm ±15 mm
External cable diameter	17.00 mm ±0.4 mm
Cable type	Class 5
Wiring certifications	VDE
Wiring standards/regulations	prEN 50620/DIN EN 50620
Cable resistance	$\leq$ 0.0033 $\Omega$ /m (based on a power core, at an ambient temperature of 20°C)

#### Standards and regulations

#### Standards

Standards/regulations	IEC 62196-2
	GB/T 20234.2-2015



1628001

https://www.phoenixcontact.com/us/products/1628001

### Classifications

UNSPSC 21.0

#### **ECLASS**

	ECLASS-11.0	27144705
	ECLASS-12.0	27144705
	ECLASS-13.0	27144705
ETIM		
	ETIM 9.0	EC002897
UNSPSC		

39121500



1628001

https://www.phoenixcontact.com/us/products/1628001

### Environmental product compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 10;
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com