

# KP HCS C-MIN-P K12 C3 P9 - Membrane keypad



2203566

<https://www.phoenixcontact.com/us/products/2203566>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Membrane keypad, self-adhesive, silver conduction technology, 12 keys, embossed, 3 colors, connecting cable: 100.5 mm, with crimp female connector, pitch: 2.54 mm, operating temperature: -20°C ... 70°C

## Your advantages

- Easy integration into HCS series electronics housings
- Membrane keypads in various sizes and colors for customized device designs
- Customization of membrane keypad via configurator

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 2203566       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | AC02          |
| Product key                          | ACFACF        |
| GTIN                                 | 4055626472492 |
| Weight per piece (including packing) | 14.7 g        |
| Weight per piece (excluding packing) | 14.7 g        |
| Customs tariff number                | 85365011      |
| Country of origin                    | DE            |

# KP HCS C-MIN-P K12 C3 P9 - Membrane keypad



2203566

<https://www.phoenixcontact.com/us/products/2203566>

## Technical data

### Product properties

|                       |   |
|-----------------------|---|
| Product type          | Membrane keypad                         |
| Housing series        | HCS                                     |
| Product family        | HCS                                     |
| Number of positions   | 9                                       |
| Pitch                 | 2.54 mm                                 |
| Housing type          | Handheld housing                        |
| Technology            | Conductive silver/graphite (T6/4 Cu/Ag) |
| Embossing             | Dome embossing 11 x 11 mm               |
| Number of socket pins | 9                                       |
| Number of keys        | 12 (4 x 3)                              |

### Dimensions

|            |                           |
|------------|---------------------------|
| Length     | 100.5 mm (Membrane cable) |
| Pitch      | 2.54 mm                   |
| Dimensions | 70 mm x 69 mm             |

### Material specifications

|                  |           |
|------------------|-----------|
| Housing material | Polyester |
|------------------|-----------|

### Environmental and real-life conditions

#### Ambient conditions

|   |                  |
|---|------------------|
| Ambient temperature (operation)         | -20 °C ... 70 °C |
| Ambient temperature (storage/transport) | -40 °C ... 80 °C |

### Mounting

|               |          |
|---------------|----------|
| Mounting type | adhesive |
|---------------|----------|

# KP HCS C-MIN-P K12 C3 P9 - Membrane keypad



2203566  
<https://www.phoenixcontact.com/us/products/2203566>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27182702 |
| ECLASS-13.0 | 27190605 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001031 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 31261500 |
|-------------|----------|

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)