


Power cable - PLD E 608-CA-MS/0,6/FS AM - 2702303

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Power cable, 3-position, PVC, orange RAL 2004, Plug straight, coding: black, on Socket straight, coding: black, cable length: 0.6 m

Product Description

The cable serves to connect multiple 600 class PLD enclosure lights in series.



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 112282
GTIN	4055626112282
Custom tariff number	85444290
Country of origin	Germany

Technical data

Dimensions

Length of cable	0.6 m
-----------------	-------

Ambient conditions

Ambient temperature (operation)	-5 °C ... 40 °C
Degree of protection	IP20
	IP40 (plugged in)

General

Rated current at 40°C	16 A
Rated voltage	250 V AC
Number of positions	3

Power cable - PLD E 608-CA-MS/0,6/FS AM - 2702303

Technical data

General

Coding	black
Insertion/withdrawal cycles	100

Material

Material, knurls	not available
------------------	---------------

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 10.0.1	27060311
eCl@ss 11.0	27060311
eCl@ss 5.0	27049000
eCl@ss 5.1	27049000
eCl@ss 6.0	27279200
eCl@ss 7.0	27279218
eCl@ss 9.0	27060311

ETIM

ETIM 6.0	EC001855
ETIM 7.0	EC001855

UNSPSC

UNSPSC 13.2	31251501
UNSPSC 19.0	31251501
UNSPSC 20.0	31251501
UNSPSC 21.0	31251501