

# VAL-MS-T1/T2 BE/O - Type 2 surge protection base element



2905650

<https://www.phoenixcontact.com/us/products/2905650>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Base element for type 1/2 arresters from the VALVETRAB MS T1/T2 product range. Version: 1-channel

## Your advantages

- Rack-mount 2U panel applications
- Plug-in direction parallel to the conductor axis
- Versions with and without floating remote indication contact
- DIN rail mounting
- Accepts Type 1 and Type 2 VAL-MS plugs
- Coding when protective plug is inserted for the first time

## Commercial data

Item number	2905650
Packing unit	12 pc
Minimum order quantity	12 pc
Sales key	CL18
Product key	CL1151
Catalog page	Page 49 (C-4-2019)
GTIN	4046356983006
Weight per piece (including packing)	95 g
Weight per piece (excluding packing)	81 g
Customs tariff number	85363030
Country of origin	US

# VAL-MS-T1/T2 BE/O - Type 2 surge protection base element



2905650

<https://www.phoenixcontact.com/us/products/2905650>

## Technical data

### Notes

#### General

Note	For installation into a touch protected cabinet. For applications with $U_C > 500$ V distances at the side and distances at the connection area must be minimum of 5 mm between different active parts including earthed parts.
------	---

### Product properties

IEC test classification	I / II T1 / T2
EN type	T1 / T2
Type	Base element, DIN rail mounting
Product type	Base element
Product family	VALVETRAB MS
Number of positions	1
Surge protection fault message	none

#### Insulation characteristics

Overvoltage category	III
Pollution degree	2

### Electrical properties

Nominal frequency $f_N$	50 Hz (60 Hz)
Nominal voltage $U_N$	500 V AC

### Connection data

Connection method	Biconnect terminal blocks
Screw thread	M5
Tightening torque	30 lb <sub>f</sub> -in. (UL)
Stripping length	16 mm
Conductor cross section flexible min.	1.5 mm <sup>2</sup>
Conductor cross section flexible max.	25 mm <sup>2</sup>
Conductor cross section, rigid min.	1.5 mm <sup>2</sup>
Conductor cross section, rigid max.	35 mm <sup>2</sup>
Conductor cross section AWG	15 ... 2 (IEC) 10 ... 2 (UL)

### Dimensions

# VAL-MS-T1/T2 BE/O - Type 2 surge protection base element



2905650

<https://www.phoenixcontact.com/us/products/2905650>

Dimensional drawing	
Width	17.6 mm
Height	77.1 mm
Depth	89.2 mm

## Material specifications

Color	black (RAL 9005) gray (RAL 7042)
Flammability rating according to UL 94	V0
Housing material	PBT

## Mechanical properties

### Mechanical data

Open side panel	No
-----------------	----

## Protective circuit

Nominal frequency $f_N$	50 Hz (60 Hz)
Maximum continuous voltage $U_C$	600 V AC
Rated load current $I_L$	80 A (with serial 16mm <sup>2</sup> through wiring) 80 A (with serial 16mm <sup>2</sup> through wiring)
Short-circuit current rating $I_{SCCR}$	25 kA
Max. backup fuse with V-type through wiring	80 A AC (gL/gG)
Max. backup fuse with branch wiring	160 A (gL/gG)

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20 IP20
Ambient temperature (operation)	-40 °C ... 80 °C
Altitude	max. 2000 m
Permissible humidity (operation)	5 % ... 95 %
Shock (operation)	25g
Vibration (operation)	5g

## Approvals

### UL specifications

SPD Type	4 (for Type 2 applications)
----------	-----------------------------

## Standards and regulations

# VAL-MS-T1/T2 BE/O - Type 2 surge protection base element



2905650

<https://www.phoenixcontact.com/us/products/2905650>

Standards/specifications	IEC 61643-1
Note	2005
Standards/specifications	EN 61643-11/A11
Note	2007

## Mounting

Mounting type	DIN rail: 35 mm
Mounting position	Horizontal, flat-mounted DIN rail, NS 35

# VAL-MS-T1/T2 BE/O - Type 2 surge protection base element



2905650

<https://www.phoenixcontact.com/us/products/2905650>

## Classifications

### ECLASS

ECLASS-11.0	27130803
ECLASS-13.0	27171292

### ETIM

ETIM 9.0	EC002496
----------	----------

### UNSPSC

UNSPSC 21.0	39121600
-------------	----------

# VAL-MS-T1/T2 BE/O - Type 2 surge protection base element



2905650

<https://www.phoenixcontact.com/us/products/2905650>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)