MACX MCR-EX-DUMMY-ISOLATOR-SP - Dummy

2905846

https://www.phoenixcontact.com/us/products/2905846

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Dummy module with no function for connecting unused intrinsically safe signal cables, with plug-in push-in connection terminal blocks.

Commercial data

Item number	2905846
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	CK31ZZ
Catalog page	Page 174 (C-5-2019)
GTIN	4046356999427
Weight per piece (including packing)	98.3 g
Weight per piece (excluding packing)	94.44 g
Country of origin	DE

Technical data

Product properties

Product type	Sample without function

Connection data

Connection method	Push-in connection
Stripping length	8 mm
Conductor cross section rigid	0.2 mm² ... 1.5 mm²
Conductor cross section flexible	0.2 mm² ... 1.5 mm²
Conductor cross section AWG	24 ... 16

Dimensions

Width	17.5 mm
Height	116 mm
Depth	113.7 mm
Depth NS 35/7,5	114.5 mm (Snapped onto DIN rail NS 35/7,5 in accordance with EN 60715)

Material specifications

Color	gray (RAL 7042)
Flammability rating according to UL 94	V0 (Housing)
Housing material	Polyamide (PA 6.6)

Environmental and real-life conditions

Ambient conditions

Ambient temperature (storage/transport)	-40 °C ... 80 °C

Mounting

Mounting type	DIN rail mounting

MACX MCR-EX-DUMMY-ISOLATOR-SP - Dummy

2905846

https://www.phoenixcontact.com/us/products/2905846

Classifications

ECLASS

ECLASS-11.0	27371392
ECLASS-13.0	27371392
ECLASS-12.0	27371392

ETIM

ETIM 9.0	EC002498

UNSPSC

UNSPSC 21.0	39121100

MACX MCR-EX-DUMMY-ISOLATOR-SP - Dummy

2905846

https://www.phoenixcontact.com/us/products/2905846

Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"