

UM-2KS50/32R/SI/J/DO24V/YCS - Active module




2908399

<https://www.phoenixcontact.com/us/products/2908399>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

32-channel, 24 V DC output relay module with screw connection and redundant, 50-pos. system connection, fuse and jumper in every output circuit, for Yokogawa ADV551 and ADV561



Commercial data

Item number	2908399
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	CK21B4
Catalog page	Page 518 (C-5-2017)
GTIN	4055626297705
Weight per piece (including packing)	857 g
Weight per piece (excluding packing)	830 g
Country of origin	DE

Technical data

Product properties

Product type	Interface module
Operating mode	100% operating factor
Mechanical service life	2x 10 ⁷ cycles

Insulation characteristics: Air clearances and creepage distances, input/output

Overvoltage category	III
Pollution degree	2

Insulation characteristics: Air and creepage distances, output/output

Insulation	Basic insulation
Overvoltage category	II
Pollution degree	2

Electrical properties

Air clearances and creepage distances, input/output

Rated insulation voltage	300 V
Rated surge voltage	6 kV (Reinforced insulation)

Air and creepage distances, output/output

Rated insulation voltage	300 V
Rated surge voltage	2.5 kV

Supported controller YOKOGAWA CENTUM VP

Suitable I/O card	ADV551
	ADV561
	NFDV551
	NFDV561

Input data

Nominal input voltage U_N	24 V DC
Input voltage range in reference to U_N	0.8 ... 1.2
Input voltage range	19.2 V DC ... 28.8 V DC
Typical input current at U_N	7 mA
Typical response time	5 ms
Typical release time	6 ms
Protective circuit	Freewheeling diode; Freewheeling diode
Status display/channel	green LED

Output data

Switching

Contact switching type	1 N/O contact
------------------------	---------------

UM-2KS50/32R/SI/J/DO24V/YCS - Active module



2908399

<https://www.phoenixcontact.com/us/products/2908399>

Type of switch contact	Single contact
Contact material	AgSnO
Maximum switching voltage	24 V DC
Minimum switching voltage	5 V (100 mA)
Limiting continuous current	1.5 A (32 °C)
	1 A (45 °C)
	0.5 A (50 °C)
Max. total current of voltage supply	10 A (50 °C)
Min. switching current	1 mA (24 V)
Interrupting rating (ohmic load) max.	48 W (24 V DC)

Connection data

Controller level

Connection method	Yokogawa KS-compatible
Number of connections	2
Number of positions	50

Field level

Connection method	Screw connection
Number of connections	32
Number of positions	2
Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Supply

Connection method	Screw connection
Number of connections	4
Number of positions	2
Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Signaling

Status display present	Yes
------------------------	-----

Dimensions

UM-2KS50/32R/SI/J/DO24V/YCS - Active module



2908399

<https://www.phoenixcontact.com/us/products/2908399>

Dimensional drawing	
Width	217.5 mm
Height	127.5 mm
Depth	60.5 mm

Material specifications

Color	green (RAL 6021)
-------	------------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP00
Degree of protection (Installation location)	≥ IP54 (Installation location)
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 80 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)

Standards and regulations

Air clearances and creepage distances, input/output

Standards/regulations	EN IEC 61010-2-201
-----------------------	--------------------

Air and creepage distances, output/output

Standards/regulations	EN IEC 61010-2-201
-----------------------	--------------------

Mounting

Mounting type	DIN rail mounting
Assembly instructions	in rows with zero spacing
Mounting position	any

Notes

General	Do not connect adjacent channels to SELV/PELV and FELV.
General	No additional touch protection is required when using a SELV/PELV voltage (≤ 25 V AC or 60 V DC).
General	At least one functional insulation against adjacent modules is complied with (in the support rail direction). If the application has stricter requirements for the insulation (basic insulation or reinforced insulation), they must be realized by applying suitable measures (e. g. partition plates).
General	Do not use for isolation

UM-2KS50/32R/SI/J/DO24V/YCS - Active module



2908399

<https://www.phoenixcontact.com/us/products/2908399>

General

For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.

UM-2KS50/32R/SI/J/DO24V/YCS - Active module



2908399

<https://www.phoenixcontact.com/us/products/2908399>

Classifications

ECLASS

ECLASS-11.0	27141152
ECLASS-13.0	27141152
ECLASS-12.0	27141152

ETIM

ETIM 9.0	EC002780
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

UM-2KS50/32R/SI/J/DO24V/YCS - Active module



2908399

<https://www.phoenixcontact.com/us/products/2908399>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
	Hexahydromethylphthalic anhydride
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com