


Wire bridge - FBSW 2-5/250MM - 3030172

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Wire bridge, length: 250 mm, width: 5.1 mm, number of positions: 1, color: red/black



The figure shows the 60 mm version

Your advantages

- ✓ Flexible potential distribution, thanks to custom wire lengths
- ✓ Bridge terminal blocks of varying terminal widths with ease
- ✓ Easy, tool-free operation, thanks to plug-in contacts



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| Minimum order quantity | 10 pc |
| GTIN |  4 055626 364667 |
| GTIN | 4055626364667 |
| Weight per Piece (excluding packing) | 1.000 g |
| Custom tariff number | 85444290 |
| Country of origin | Poland |

Technical data

Technical data

| | |
|---------------------|-----------|
| Color | red/black |
| Material | CuSn |
| Number of positions | 1 |
| Length | 250 mm |
| Height | 4.7 mm |

Wire bridge - FBSW 2-5/250MM - 3030172

Technical data

Technical data

| | |
|--|---|
| Width | 5.1 mm |
| Flammability rating according to UL 94 | V0 |
| Maximum load current | 10 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.) |

Standards and Regulations

| | |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27141190 |
| eCl@ss 11.0 | 27141190 |
| eCl@ss 4.0 | 27141100 |
| eCl@ss 4.1 | 27141100 |
| eCl@ss 5.0 | 27141100 |
| eCl@ss 5.1 | 27141100 |
| eCl@ss 6.0 | 27141100 |
| eCl@ss 7.0 | 27141190 |
| eCl@ss 9.0 | 27141190 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001456 |
| ETIM 3.0 | EC001456 |
| ETIM 4.0 | EC001456 |
| ETIM 6.0 | EC002848 |
| ETIM 7.0 | EC002848 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39121421 |

Wire bridge - FBSW 2-5/250MM - 3030172

Classifications

UNSPSC

| | |
|-------------|----------|
| UNSPSC 18.0 | 39121410 |
| UNSPSC 19.0 | 39121410 |
| UNSPSC 20.0 | 39121410 |
| UNSPSC 21.0 | 39121410 |